

TOWNSHIP 21 RANGE 09 POINT IDENTIFIER # 200400

PRIMARY CORNER DESCRIPTION Cor. Secs. 17, 18, 19, & 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Alonzo Gesner, Deputy Surveyor, under Contract #608, dated April 17, 1893 - (DCSO rec. Vol. 2 Page(s) 973-4)

Set sandstone 20x14x8" 15" in the ground on steep hill sloping SE for cor to secs. 17, 18, 19, & 20 marked with 3 notches on the S and 5 notches on the E edges, from which
An Alder, 6" dia., bears N.16°30'E., 19 lks., mkd: T21S R9W S17 BT.
A Maple, 5" dia., bears S.9°E., 26 lks., mkd: T21S R9W S20 BT.
An Alder, 6" dia., bears S.78°W., 58 lks., mkd: T21S R9W S 19 BT.
A D.Fir, 15" dia., bears N.34°W., 26 lks., mkd: T21S R9W S18 BT.

Les Roberts LS #1039, Triangle Engineering Co. - For: International Paper Co. - Nov. 1979 - M 81-45

Found - 20"x14"x8" notched stone (Orig.)
20" Fir stub bears N.34°W., 17.2 ft. (1894 BT)
18" Maple bears S.9°E., 17.2 ft. (1894 BT)
Set - 1½" iron pipe & brass cap, buried stone beside pipe.
38" Fir bears N.34°W., 36.7 ft.
34" Fir bears S.35°W., 28.6 ft.
32" Fir bears N.34°E., 8.3 ft.