

TOWNSHIP 21 RANGE 9 POINT IDENTIFIER # 200640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 5 & 6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by William Thiel under contract 260 dated April 17, 1877 - (DCSO records Vol. 2 Page(s) 885)

-----  
Set ¼ sec. post bet. sec. 6 & 5, from which  
A Chittewood, 12" dia., bears N.36¼°W., 23 lks.  
A Maple, 36" dia., bears N.6¼°E., 81 lks.

GLO survey by Alonzo Gesner, Deputy Surveyor, under Contract #608, dated April 17, 1893 - (DCSO rec. Vol. 2 Page(s) 984)

-----  
The ¼ sec. cor., is a post, 3 ft. above ground, 2" sq., mkd. ¼ S on the W face, from which  
A Chittewood, 14" dia., bears N.36°15'W., 23 lks., mkd. ¼ S BT.  
A Maple, 40" dia., bears N.6°15'E., 83 lks., mkd. ¼ S BT.  
Practically agreeing with notes furnished me by the U.S. Surveyor General.

Richard J. Hintz, PLS #497 - For: International Paper Co. - Aug. 1982 - M 92-74

-----  
Set - 1¼"x36" IP w/brass cap stamped PLS 497  
92" Maple bears N.53°E., 36.0 ft. (scribed)  
24" Maple bears N.56°W., 59.9 ft. (scribed)  
Note - distances to a 50d nail in the face of each BT.