

TOWNSHIP 21 RANGE 09 POINT IDENTIFIER # 240100

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 32 only

|             |                   |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

GLO survey by Alonzo Gesner, Deputy Surveyor, under Contract #608 -dated April 17, 1893 - (DCSO records Vol. 2 Page(s) 899)

-----

Set Fir post, 4½ ft. long, 4" sq., 24" in the ground, for ¼ sec. cor., mkd. ¼ S on the N. fce, from which

A Fir 12" dia., bears S.72°30'E., 76 lks. dist. mkd. ¼ S BT.

A Fir 10" dia., bears N.33°30'W., 46 lks. dist. mkd. ¼ S BT.

BLM resurvey by Joel E. Robb, Cadastral Surveyor, under Group #1281, surveyed Aug/Oct. 1985 - (DCSO records Vol. 48 Page(s) 18189)

-----

The ¼ sec. cor. of sec. 32 only, determined from the original bearing trees:

A Fir 30" dia., bears S.72½°E., 79 lks. dist., with healed blaze. (Rec. 76 lks.)

A Fir 30" dia., bears N.33½°W., 46 lks. dist., with scribe marks 32 visible on opened blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T 21 S R 9 W

¼ S 32

1985

from which a new bearing tree

A Fir 30" dia., bears N.58¼°E., 66 lks. dist. mkd. ¼ S32 BT.