

TOWNSHIP 21 RANGE 09 POINT IDENTIFIER # 240400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 17 & 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Alonzo Gesner, Deputy Surveyor, under Contract #608, dated April 17, 1893 - (DCSO rec. Vol. 2 Page(s) 974-5)

Set Alder post, 4½ ft. long, 4" sq., 24" in the ground for ¼ Sec. cor. mkd. ¼ S on the N face, from which
 A D.Fir, 40" dia., bears S.86°E., 35 lks., mkd: ¼ S BT.
 A D.Fir, 20" dia., bears N.31°W., 137 lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - Milo E. Godfrey & crew - Oct. 20, 1964 - C.S. File 52/14-136

Corner searched for not found.

Les Roberts LS #1039, Triangle Engineering Co. - For: International Paper Co. - Nov. 1979 - M 81-45

Set - 1½" iron pipe & brass cap
 22" Fir bears S.86°E., 5.3 ft.
 16" Fir bears N.13°W., 19.9 ft.
Note - Corner was set by single proportionate measure.