

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Alonzo Gesner, Deputy Surveyor, under Contract #608, dated April 17, 1893 - (DCSO rec. Vol. 2 Page(s) 955)  
 -----  
 Set Hemlock post 5 ft. long 4" sq., 24" in the ground on hill side slope E for cor. to secs. 28, 29, 32, & 33. Marked T21 S S28 on the NE., R9W S33 on the SE, S 32 on the SW and S29 on the NW faces with 1 notch on the S & 4 notches on the E edges, from which  
 A Fir, 28" dia., bears N.18°E., 80 lks., mkd: T21S R9W S28 BT.  
 A Maple, 8" dia., bears S.73°15'E., 79 lks., mkd: T21S R9W S33 BT.  
 A Maple, 6" dia., bears S.36°30'W., 10 lks., mkd: T21S R9W S32 BT.  
 A Fir, 60" dia., bears N.33°45'W., 65 lks., mkd: T21S R9W S29 BT.

BLM dependent resurvey by Peter A. Peterson, Cadastral Surveyor, under Group #350 & 511, surveyed April 1966/May 1967 - (DCSO records, Vol. 34 Page(s) 14249)  
 -----  
 The cor. of secs. 28, 29, 32 & 33, determined at the record bearing & dist. from each of the remaining orig. BTs:  
 A decayed Fir stump, 20" dia., bears N.18°E., 80 lks., with no marks remaining.  
 A Maple, 22" dia., bears S.73¼°E., 79 lks., with scribe marks S 3 visible on opened blaze.  
 A Maple crown, 20" dia., bears S.36½°W., 10 lks., with no marks remaining.  
 A Fir, 88" dia., bears N.33¾°W., 57 lks., with no marks visible on partially opened blaze. (Slope dist., 65 lks., record, 65 lks.)  
 At the corner point  
 Set an iron post, 28" long, 2½" dia., 25" in the ground, with brass cap marked:  

T 21	S R 9 W
S 29	S 28
S 32	S 33
1966	

 from which new BTs  
 A Fir, 11" dia., bears N.47°E., 99 lks., mkd: T21S R9W S28 BT.  
 A Maple, 35" dia., bears S.33°W., 61 lks., mkd: T21S R9W S32 BT.

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Douglas Co. Surveyors Office - Gary Langlitz - Pete Earle - Jan. 15, 1975 - C.S. File 56/49-1

-----

Found - 1966 BLM brass cap, out of the ground, laying at the base of the Orig. NW BT.  
 88" D.Fir bears N.33¾°W., 37.6 ft. (to the face of the tree) an orig. BT being previously opened, no marks visible.  
 The remains of an Orig. BT a 20" decayed fir stump bears N.18°E., 52.8 ft. (to the face) no marks remaining.  
 35" now 36" big leaf maple, bears S.36°W., 40.3 ft. (rec. S.33°W., 40.3 ft.) with a healed blaze.  
 All remaining orig. & 1966 resurvey corner accessories have been displaced or destroyed due to recent road building and a subsequent landslide. Since the corner location is in the slide area:

Set - A brass cap as a witness corner 55' west of the true corner mkd: COUNTY SURVEYORS T 21 S R 9 W  
 OFFICE WIT. COR.  
 1974 S 29 | S 28  
 S 32 | S 33  
 55' east to cor

from which I mark the following BTs:  
 18" Hemlock, bears N.10°W., 21.0 ft. scribed "WC T21S R9W S29 CS BT"  
 24" big leaf maple bears S.32½°W., 52.2 ft. scribed "WC T21S R9W S32 CS BT"  
 No trees suitable to the NE & SE  
 This witness corner lies approx. 70 ft. west of newly constructed dirt road.

Douglas Co. Surveyors Office - Randall Smith - John Pike - May 20, 1992 - C.S. File 64/26-10

-----

Found - 2½" dia., DCSO brass cap mkd: T21S R9W Wit. Cor. S28 S29 S32 S33 55 ft. EAST to Corner 1974 cap sits on 1½" O.D. IP and protrudes 5" above ground.  
 18" now 24" dia., Hemlock with a partially healed double blaze illegible scribing visible, bears N.10°W., 21.0 ft. 1974  
 24" now 23" dia., Maple with a partially healed single blaze, scribing visible "WC T21S R9W S32 CS BT" bears S.31°W., 52.2 ft. (rec. S.32½°W., 52.2 ft.) 1974

continued next page

TOWNSHIP 21 RANGE 09 POINT IDENTIFIER # 300200

PRIMARY CORNER DESCRIPTION Cor Secs 28, 29, 32, & 33

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New - 60" now 95" dia. D.Fir with a previously opened healed blaze, blaze faces southeast, bears N.42½°E., 49.0 ft. (OBT)  
35" now 33" dia., Maple with a fully healed double blaze, blaze faces northeast, bears S.45°E., 44.1 ft. (1966 resurvey)  
18" dia., Maple double blazed and scribed "WC T21S R9W S33 CS BT" bears S.18°E., 16.5 ft.

Clyde Mulkins - For: I.P. Timberlands - Jan./Feb. 1996 - M141-61  
-----  
Reset - I reset a 1966 BLM monument (monument was moved in land slide) at the corner of secs 28, 29, 32 & 33  
Found - Orig. 29" Maple face buried bears S.72°E., 52.1 ft. (rec. S.73¼°E., 79 lks.)  
A 34" Maple with a healed face bears S.35°W., 40.3 ft. (Rec. S.33°W., 61 lks.)  
Orig. 90" D.Fir with scribes (opened up face) bears N.33°W., 37.6 ft. (rec. N.33¾°W., 57 lks.)  
Douglas Co. brass cap (witness corner) bears N.89°47'36"W., 54.44 ft. (Rec. West 55.0 ft.)