

PRIMARY CORNER DESCRIPTION Cor. Secs 20, 21, 28, & 29

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Alonzo Gesner, Deputy Surveyor, under Contract #608, dated April 17, 1893 - (DCSO rec. Vol. 2 Page(s) 957)

-----

Set Hemlock post, 5 ft. long 6" sq., 24" in the ground for cor. to secs. 20, 21, 28 & 29. Marked T21S S21 on the NE, R9W S28 on the SE, S29 on the SW and S20 on the NW faces with 2 notches on the S & 4 notches on the E edges, from which

- A Hemlock, 10" dia., bears N.37°15'E., 22 lks., mkd: T21S R9W S21 BT.
- A Hemlock, 24" dia., bears S.18°15'E., 10 lks., mkd: T21S R9W S28 BT.
- A Hemlock, 20" dia., bears S.58°15'W., 47 lks., mkd: T21S R9W S29 BT.
- A Hemlock, 16" dia., bears N.15°45'W., 16 lks., mkd: T21S R9W S20 BT.

BLM dependent resurvey by Peter A. Peterson, Cadastral Surveyor, under Group #350 & 511, surveyed April 1966/May 1967 - (DCSO records, Vol. 34 Page(s) 14250)

-----

Point for the cor. of secs. 20, 21, 28, & 29 at proportionate distance; there is no remaining evidence of the orig. corner. This point falls in dirt road, 25 lks. wide, which bears N.40°E. and S.40°W.

Set an iron post, 28 long, 2½" dia., 40" in the ground, with brass cap marked:

T 21 S	R 9 W
<u>S 20</u>	<u>S 21</u>
S 29	S 28
1966	

from which

- An Alder, 5" dia., bears N.16½°E., 68 lks., mkd: T21S R9W S21 BT.
- A Fir, 5" dia., bears S.61°E., 126 lks., mkd: T21S R9W S28 BT.
- A Hemlock, 12" dia., bears S.27¼°W., 246 lks., mkd: T21S R9W S29 BT.
- A Fir, 5" dia., bears N.49½°W., 136 lks., mkd: T21S R9W S20 BT.

Clyde Mulkins - For: I.P. Timberlands - Jan./Feb. 1996 - M141-61

-----

Found - 1966 BLM brass cap  
 13" Alder with visible bark scribes bears N.16½°E.,  
 68 lks.  
 continued next page

TOWNSHIP 21 RANGE 9 POINT IDENTIFIER # 300300

PRIMARY CORNER DESCRIPTION Cor. Secs 20, 21, 28, & 29

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

19" D.Fir with a healed face bears S.61°E., 126 lks.  
24" Hemlock with healed face bears S.27¼°W., 246 lks  
Corner falls in the center of a gravel road.  
Corner is buried approx 2 ft. deep.  
I set a 6" spike over the fd. brass cap.

Fd. Ok by Gary Smithers, 12/2000 - C.S. File 65/33-27