

TOWNSHIP 21 RANGE 09 POINT IDENTIFIER # 300340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 20 & 21

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Alonzo Gesner, Deputy Surveyor, under Contract #608, dated April 17, 1893 - (DCSO rec. Vol. 2 Page(s) 959)

A Cedar 14" dia., I marked it $\frac{1}{4}$ S on the W side for $\frac{1}{4}$ Sec. cor., from which
A Cedar, 24" dia. bears N.79°30'E., 22 lks. mkd: $\frac{1}{4}$ S BT.
A Cedar, 10" dia. bears N.77°30'W., 30 lks. mkd: $\frac{1}{4}$ S BT.

BLM dependent resurvey by Peter A. Peterson, Cadastral Surveyor, under Group #350 & 511, surveyed April 1966/May 1967 - (DCSO records, Vol. 34 Page(s) 14251-2)

The $\frac{1}{4}$ Sec. cor. secs. 20 & 21, occupied by the orig. corner tree, a Cedar, 28" dia., with a healed blaze on W. face, from which the orig. BTs:
A Cedar, 34" dia., bears N.79 $\frac{1}{2}$ °E., 22 lks., with healed blaze.
A Cedar, 13" dia., bears N.77 $\frac{1}{2}$ °W., 30 lks., with fragmentary scribe marks visible on open blaze.
I add a reference monument,
An iron post, 28" long, 2 $\frac{1}{2}$ " dia., 24" in the ground, for a reference monument, bears N.45°W., 20 lks., with brass cap marked $\frac{1}{4}$ S20 RM and an arrow pointing to the corner.