TOWNSHIP 21 RANGE 09 POINT IDENTIFIER # 300440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 16 & 17

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Alonzo Gesner, Deputy Surveyor, under Contract #608, dated April 17, 1893 - (DCSO rec. Vol. 2 Page(s) 961)

A rock in place 24x24x8 ins. above ground marked ¼ on the W side with X at the exact point for ¼ sec. cor. from which
A d. cedar, 8" dia., bears S.50°E., 22 lks., mkd: ¼ S BT.
A Fir, 18" dia., bears S.36°W., 60 lks., mkd: ¼ S BT.

BLM dependent resurvey by Peter A. Peterson, Cadastral Surveyor, under Group #350 & 511, surveyed April 1966/May 1967 - (DCSO records, Vol. 34 Page(s) 14253)

Point for the ¼ sec. cor. of secs. 16 & 17 , at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28 long, 2½" dia., 24" in the ground with brass cap marked: ¼
S 17|S 16
T 21 S R 9 W
1966
from which
A Fir, 14" dia., bears N.75°E., 20 lks., mkd: ¼ S16 BT.
A Fir, 14" dia., bears N.61°W., 29 lks., mkd: ¼ S17 BT.

Tony Hostetter - For: Roseburg Resources - 7/28/2023 - C.S. File 63/113-11

Found - 1966 BLM brass cap (Vol 34, PG 14253) from which:
24" fir, 1966 BT, face evident, BLM tag bears; N.61°W., 19.1 ft to center.
New BTs- 8" fir, marked "X", BT tag, bears, N.03°13'E., 45.4 ft to spike, placed in root collar below tag.
10" Maple marked "X", BT tag, bears; S.20°46'E., 27.2 ft to spike, placed in root collar below tag
28" Fir, marked "X", BT tag, bears; S.10°26'E. 30.8' ft to spike, placed in root collar below tag
Bearings based on 1965 BLM Survey.