

TOWNSHIP 21 RANGE 09 POINT IDENTIFIER # 300500

PRIMARY CORNER DESCRIPTION Cor Secs 8, 9, 16, & 17

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Alonzo Gesner, Deputy Surveyor, under Contract #608, dated April 17, 1893 - (DCSO rec. Vol. 2 Page(s) 961-2)

Set sandstone 16x8x6" in the ground on steep hill side sloping NE for cor. to secs. 8, 9, 16, & 17, marked with 4 notches on the S & E edges, from which

- A Fir, 60" dia., bears N.82°E., 325 lks., mkd: T21S R9W S9 BT.
- A D.Fir, 50" dia., bears S.37°E., 65 lks., mkd: T21S R9W S16 BT.
- A Dogwood, 4" dia., bears S.52°30'W., 55 lks., mkd: T21S R9W S17 BT.
- A D.Fir, 50" dia., bears N.66°15'W., 50 lks., mkd: T21S R9W S8 BT.

BLM dependent resurvey by Peter A. Peterson, Cadastral Surveyor, under Group #350 & 511, surveyed April 1966/May 1967 - (DCSO records, Vol. 34 Page(s) 14253-4)

The cor. of secs. 8, 9, 16, & 17, monumented with the orig. sandstone, 16x8x6", extending 6" above ground, firmly set, marked with 4 grooves on S & E faces, from which the remains of the orig. BTs:

- A Fir snag, 60" dia., bears S.37°E., 55 lks., with healed blaze. (Slope dist., 65 lks., rec. 65 lks.)
- A Fir root crown, 60" dia., bears N.66¼°W., 50 lks., with no marks remaining.

At the corner point

Set an iron post, 28" long, 2½" dia., 22" in the ground, with brass cap marked:

T 21 S R 9 W
S 8 | S 9
S 17 | S 16
1966

from which new BTs

- A Fir, 18" dia. bears N.57½°E. 54 lks. mkd: T21S R9W S9 BT
- A Fir, 20" dia., bears S.61½°E., 21 lks., mkd: T21S R9W S16 BT.
- A Fir, 17" dia. bears S.29°W. 43 lks. mkd: T21S R9W S8 BT.
- A Fir, 20" dia., bears N.77°W., 37 lks., mkd: T21S R9W S8 BT.

Deposit the orig. sandstone alongside the iron post.

Tony Hostetter - For: Roseburg Resources - 7/28/2023 - C.S. File 63/113-12

Found - 1966 BLM brass cap (Vol 34, PG 14253-4) from which:
20" Fir stump, 1966 BT, face evident, BLM tag bears;
S.61½°E., 13.9 ft to center. Continued next pg

TOWNSHIP 21 RANGE 09 POINT IDENTIFIER # 300500

PRIMARY CORNER DESCRIPTION Cor Secs 8, 9, 16, & 17

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

New BTs- 38" Fir, marked "X", BT tag, bears; N.47°07'E., 48.9
ft to spike, placed in root collar below tag.
10" Fir, marked "X", BT tag, bears; S.28°04'W., 16.2
ft to spike, placed in root collar below tag.
8" Alder, marked "X", BT tag, bears; S.56°41'E.,
10.6 ft to spike, placed in root collar below tag
Bearings based on 1965 BLM Survey.