TOWNSHIP 21 RANGE 09 POINT IDENTIFIER # 300540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 8 & 9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Alonzo Gesner, Deputy Surveyor, under Contract #608, dated April 17, 1893 - (DCSO rec. Vol. 2 Page(s) 963)

Set sandstone 12x8x6", 9" in the ground on steep hill side sloping North for ¼ sec. cor. marked ¼S on the W face, from which

A D.Fir, 40" dia., bears S.59°30'W., 48 lks., mkd: ¼ S BT.
A Fir, 18" dia., bears N.52°E., 43 lks., mkd: ¼ S BT.

BLM dependent resurvey by Peter A. Peterson, Cadastral Surveyor, under Group #350 & 511, surveyed April 1966/May 1967 - (DCSO records, Vol. 34 Page(s) 14259)

Point for the ¼ sec. cor. of secs. 8 & 9, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 18 long, 1" dia., 10" into drill hole, in solid rock, with brass cap marked:

¼
S 8|S 9
T 21 S R 9 W
1966

from which

A Fir, 12" dia., bears N.58°E., 29 lks., mkd: ¼ S9 BT.
A Fir, 15" dia., bears S.60°W., 17 lks., mkd: ¼ S8 BT.

Fd. Ok by L. Roberts Nov. 1981 - M 90-13