

PRIMARY CORNER DESCRIPTION Cor. Secs. 4 & 5, only (South)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by F.M. Johnson, Deputy Surveyor, under Contract #314, dated Dec. 27, 1878 - (DCSO rec. Vol. 2 Page(s) 886)

-----

Set rock 40x14x24" for cor. to secs. 4, 5, 8, & 9, from which

- A Fir, 44" dia., bears N.47°E., 107 lks.
- A Fir, 40" dia., bears S.41°E., 124 lks.
- A Fir, 24" dia., bears S.83°W., 66 lks.
- A Fir, 48" dia., bears N.43°W., 135 lks.

GLO survey by Alonzo Gesner, Deputy Surveyor, under Contract #608, dated April 17, 1893 - (DCSO rec. Vol. 2 Page(s) 964-5)

-----

At the SE corner of Sec. 5, which is a rock in place 40x24x10" above ground on steep hill side sloping SW, marked with a X on top of stone, the other marks had been scaled off by a large tree falling on it. I remarked stone with 5 notches on the S and 4 notches on the E edges, from which

- A Fir, 48" dia. bears N.47°E., 107 lks., marks grown over.
- A Fir, 40" dia., bears S.41°E., 124 lks., marks burned out by resent forest fires.
- A Fir, 24" dia., bears S.83°W., 66 lks., I remark this tree T 21 S R 9 W S 4 & 5 BT.
- A Fir, 48" dia., bears N.43°W., 135 lks., marked T 21 S R 9 W S 5 BT.

This corner agrees with description furnished me by U.S. Surveyor General.

BLM dependent resurvey by Peter A. Peterson, Cadastral Surveyor, under Group #350 & 511, surveyed April 1966/May 1967 - (DCSO records, Vol. 34 Page(s) 14255)

-----

The cor. of secs. 4 & 5 only, on the N bdy of sec. 8 monumented with the orig. sandstone 40x24x12", extending 12" above ground, firmly set, marked with 4 grooves on E face, from which the orig. BTs:

- A Fir, 70" dia., bears S.46°E., 124 lks., with healed blaze. (Rec. S.41°E.)
- A Fir, 35" dia., bears S.87°W., 60 lks., with fragmentary scribe marks visible on partially healed blaze. (Rec. S.83°W., 66 lks.)
- A Fir snag, 58" dia., bears N.43°W., 135 lks., with healed blaze.

At the corner point  
Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked:

T 21 S R 9 W  
S 5 | S 4  
 S 8

1966 continued next page

TOWNSHIP 21 RANGE 09 POINT IDENTIFIER # 300600

PRIMARY CORNER DESCRIPTION Cor. Secs. 4 & 5, only (South)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which new BTs  
A Fir, 16" dia. bears N.71°E., 8 lks. mkd: T21S R9W S4 BT.  
A Fir, 18" dia. bears N.39°W. 36 lks. mkd: T21S R9W S5 BT.  
Deposit the orig. sandstone alongside the iron post.

Fd. Ok by Les Roberts, Dec. 1982 - M 90-30