TOWNSHIP 21 RANGE 09 POINT IDENTIFIER # 300640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 4 & 5

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by F.M. Johnson, Deputy Surveyor, under Contract #314, dated Dec. 27, 1878 - (DCSO rec. Vol. 2 Page(s) 886)

Set ¼ sec. post from which
A Hemlock, 26" dia., bears S.76°W., 16 lks.
A Maple, 16" dia., bears S.71°E., 74 lks.

GLO survey by Alonzo Gesner, Deputy Surveyor, under Contract #608, dated April 17, 1893 - (DCSO rec. Vol. 2 Page(s) 985)

The ¼ sec. which is a post marked ¼ S on the W face, from which
A Maple, 20" dia., bears S.71°E., 75 lks., mkd: ¼ S BT.
A Hemlock, 30" dia., bears S.76°W., 16 lks., mkd: ¼ S BT.

BLM dependent resurvey by Peter A. Peterson, Cadastral Surveyor, under Group #350 & 511, surveyed April 1966/May 1967 - (DCSO records, Vol. 34 Page(s) 14260)

Point for the ¼ sec. cor. of secs. 4 & 5, at proportionate dist.; there is no remaining evidence of the orig. corner. Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked: ¼
S 5|S 4
T 21 S R 9 W
1966
from which
A Maple, 20" dia., bears S.50°E., 70 lks., mkd: ¼ S4 BT.
A Fir, 28" dia., bears S.57°W., 62 lks., mkd: ¼ S5 BT.

Fd. Ok by Les Roberts, Dec. 1982 - M90-30