

PRIMARY CORNER DESCRIPTION CC Cor. Secs. 8 & 9 (North)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Alonzo Gesner, Deputy Surveyor, under Contract #608, dated April 17, 1893 - (DCSO rec. Vol. 2 Page(s) 964)

To a point 27.63 chs. N.89°33'E., of the SE corner of Sec. 5, set Alder post 4½ ft. long, 4" sq. 24" in the ground at the point of intersection on hill side sloping E and on West side of large Cedar log for closing corner to secs. 8 & 9. Marked CC T21S R9W on the S., S9 on the E and S8 on the W. faces with 5 grooves on the S & r grooves on the E faces, from which

- A Fir, 36" dia., bears S.65°30'E., 160 lks., mkd: T21S R9W S9 BT.
- An Alder, 8" dia., bears S.66°30'W., 10 lks., mkd: T21S R9W S8 BT.
- A Cherry, 6" dia., bears N.14°E., 33 lks., mkd: CC T21S R9W S8 and S9 BT.

BLM dependent resurvey by Peter A. Peterson, Cadastral Surveyor, under Group #350 & 511, surveyed April 1966/May 1967 - (DCSO records, Vol. 34 Page(s) 14256)

The closing cor. of secs. 8 & 9, determined at record bearing & dist. from the only remaining orig. BT:

- A Fir, 36" dia., bears S.65½°E., 160 lks., with healed blaze.

At the corner point

Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked:

S 4
S 8 | S 9
CC
T 21 S R 9 W
1966

from which

- A Cedar, 15" dia., bears S.11°E., 41 lks., mkd: T21S R9W S9 CC BT.
- A Fir, 20" dia., bears S.80°W., 23 lks., mkd: T21S R9W S8 CC BT.