

TOWNSHIP 21 RANGE 09 POINT IDENTIFIER # 336100

PRIMARY CORNER DESCRIPTION No. 1/4 Cor. Sec. 4 only, T22-9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

V. W. Hosford - For: Evans Products Co. - Aug. 1954 - C.S.
File 41/292 and M 10-80

At proportionate distance, I establish the North $\frac{1}{4}$ S 4. At
this corner, I set a 4" Fir post marked " $\frac{1}{4}$ S4 PS 253", from
which

A Fir 40" dia. bears S.57°E., 87.0 ft. marked $\frac{1}{4}$ S4 PS 253
BT.

Douglas County Surveyors Office - John M. Powell, Deputy -
C.S. File 53/66-135 - Sept. 1971

Corner searched for, not found.

Dependent resurvey by Boyd W. Peterson & John A. Farmer,
Cadastral Surveyors, under Group #1791, surveyed Oct.
1995/Feb. 1998. (DCSO records Vol. 52 Page(s) 19858-9)

Point for the $\frac{1}{4}$ sec. cor. of sec. 4 only, T. 22 S., R. 9 W.
Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24
ins. in the ground, with brass cap mkd.

T21S
 $\frac{1}{4}$ S 4
T22S R9W
1996

from which

A fir, 9" diam., bears S.80 $\frac{1}{4}$ °E., 10 $\frac{1}{2}$ lks., mkd. $\frac{1}{4}$ S4 BT.

A fir, 6" diam., bears S.65 $\frac{1}{2}$ °W., 18 $\frac{1}{2}$ lks., mkd. X BT.

Deposit a magnet in a white plastic case at base of stainless
steel post.