

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 21 & 28

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Alonzo Gesner, Deputy Surveyor, under Contract #608, dated April 17, 1893 - (DCSO rec. Vol. 2 Page(s) 958)

-----  
Set Hemlock post 4½ ft. long, 4" sq., 24" in the ground for ¼ sec. cor. marked ¼S on the N. face, from which  
A Hemlock, 24" dia., bears N.47°E., 75 lks. mkd: ¼ S BT.  
A Hemlock, 30" dia., bears S.33°30'W, 15 lks, mkd: ¼ S BT.

BLM dependent resurvey by Peter A. Peterson, Cadastral Surveyor, under Group #350 & 511, surveyed April 1966/May 1967 - (DCSO records, Vol. 34 Page(s) 14250-1)

-----  
The corner of secs. 21 & 28, determined at record bearing & distance from the orig. BTs:

A sawed Hemlock stump, 38" dia., bears N.47°E., 75 lks. with scribe marks ¼ S visible on opened blaze.  
A sawed Hemlock stump 22" dia., bears S.33½°W., 15 lks., with scribe mark S visible on opened blaze.

At the corner point

Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked: ¼  $\frac{S \ 21}{S \ 28}$   
T 21 S R 9 W  
1966

from which new BTs

A Fir, 6" dia., bears N.73½°E., 179 lks., mkd: ¼ S21 BT.  
A Hemlock, 21" dia. bears S.10°E. 242 lks. mkd: ¼ S28 BT.

David Edwards - For: Roseburg Resources - June 2000 - M 135-6  
Found - BLM brass cap  
16" Fir N.73°E., 118.2 ft.  
21" Fir N.15°W., 13.5 ft.  
28" Hemlock, S.10°E., 159.7 ft.

Clyde Mulkins - For: I.P. Timberlands - Jan./Feb. 1996 - M141-61

-----  
Found - 1966 BLM brass cap  
The remains of the orig. Hemlock stump (no marks remaining) bears S.33½°W., 15 lks.  
15" D.Fir with healed face bears N.73½°E., 179 lks.  
32" Hemlock with healed face bears S.10°E., 242 lks.  
21" D.Fir with healed face (orig. unknown) bears S.54°E., 29.0 ft.  
New - Scribed "¼ S21 BT" on 21" DF bears N.15°W. 13.5 ft  
Corner falls approx. 50' West of old road.