

PRIMARY CORNER DESCRIPTION South 1/4 Cor. Sec. 4 only

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by Alonzo Gesner, Deputy Surveyor, under Contract #608, dated April 17, 1893 - (DCSO rec. Vol. 2 Page(s) 965)

Set sandstone 16x7x6" 12" in the ground on point of hill projecting SW for ¼ sec. cor. mkd ¼ on the N face, from which
A Fir, 12" dia., bears N.58°E., 44 lks., mkd: ¼ S BT.
A Maple, 10" dia., bears S.12°E., 75 lks., mkd: ¼ S BT.

BLM dependent resurvey by Peter A. Peterson, Cadastral Surveyor, under Group #350 & 511, surveyed April 1966/May 1967 - (DCSO records, Vol. 34 Page(s) 14256)

The ¼ sec. cor. of sec. 4 only, monumented with a sandstone, not of rec., 14x12x8", extending 8" above ground, firmly set, mkd. CS on S face, from which the orig. BTs:

A Fir, 38" dia., bears N.58°E., 44 lks., with scribe marks
BT visible on open blaze.

A Maple, 27" dia., bears S.20°E., 83 lks., with no marks remaining on opened & rotted blaze. (Rec. S.12°E., 75 lks.)

And a BT not of record

A Fir, 30" dia. bears S.24½°E., 18 lks. with healed blaze.

At the corner point

Set an iron post, 28" long, 2½" dia., 22" in the ground, with brass cap marked:

T 21 S R 9 W

¼ S 4

1966

from which a new BT

A Fir, 48" dia., bears N.15°W., 60 lks., mkd: ¼ S4 BT.

The corner is located on the point of a spur, slopes SW.