

TOWNSHIP 21 RANGE 09 POINT IDENTIFIER # 400200

PRIMARY CORNER DESCRIPTION Cor Secs 27, 28, 33, & 34

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by Alonzo Gesner, Deputy Surveyor, under Contract #608, dated April 17, 1893 - (DCSO rec. Vol. 2 Page(s) 941)

-----

Set sandstone 14 x 12 x 5" 9" in the ground, for cor. of secs. 27, 28, 33 & 34, marked with 1 notch on the S and 3 notches on the E faces; from which

- A Maple, 10" dia., bears N.62°E., 12 lks., mkd: T21S R9W S27 BT.
- A Cedar, 48" dia., bears S.53°30'E., 67 lks., mkd: T21S R9W S34 BT.
- A Vine Maple, 6" dia., bears S.58°30'W., 61 lks., mkd: T21S R9W S33 BT.
- A Cedar, 45" dia., bears N.85°15'W., 45 lks., mkd: T21S R9W S28 BT.

Douglas Co. Surveyors Office - John M. Powell -May 24, 1971 - C.S. File 53/66-9

-----

Condition report, reported as found  
Found - 1½" iron pipe.  
BLM tags on large fir stump N.80°W., 48' & large Cedar stump S.40°W., 51'.  
This iron pipe fits calls east 1 chain & north 6 chains fairly good.  
I do not find orig. BTs. area logged & burnt.

David Edwards - For: Roseburg Resources - June 2000 - M 135-6 Cor. Secs. 27, 28, 33, & 34

-----

Found - 1½"x40" Iron pipe, fits calls to creeks east, west, & north within reason.  
11" Alder, N.38°E., 8.55 ft.  
16" Alder S.27½°E., 10.05 ft.  
New BTs- 9" Alder S.59°W., 11.17 ft.  
11" Alder N.73°W., 15.65 ft.

BLM Dependent resurvey by Joseph M. Mannix, Cadastral Surveyor under Group No. 2721, surveyed June/Aug. 2013 - (DCSO records Vol. 58 Page(s) 23168-9)

-----

The cor. of secs. 27, 28, 33, & 34, restored by person(s) unknown, and perpetuated by Edwards, in 2000. There is no remaining evidence of the original cor. & this position is accepted as the best available evidence of the cor.; monumented with a steel pin, 5/8" dia., firmly set, projecting 6" above ground, with an aluminum cap (properly) mkd. from which the remains of the bearing trees mkd. by Edwards

continued next page

TOWNSHIP 21 RANGE 09 POINT IDENTIFIER # 400200

PRIMARY CORNER DESCRIPTION Cor. Secs. 27, 28, 33, & 34

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A root hole bears N.38°E., 8.6 ft., alongside of which is a down alder, 11" dia., with illegible scribe marks visible on open decayed blaze.

An alder, 18" dia., bears S.30¾°E., 10.0 ft., with scribe marks S34 BT visible on partially healed blaze.

An alder, 13" dia., bears S.54¾°W., 10.4 ft., with scribe marks S33 BT visible on partially healed blaze.

An alder, 12" dia., bears N.67¾°W., 15.5 ft., with scribe marks S28 BT visible on decayed partially healed blaze.

At the corner point

Set a stainless steel post, 28" long, 2½" dia., 23" in the ground, directly over the steel pin, with a brass cap mkd.

T 21	S	R 9	W
S 28		S 27	
S 33		S 34	
2013			

from which a new bearing tree

An alder, 16" dia., bears N.80°E., 27.1 ft., mkd. T21S R9W S27 BT on bark.

Lying alongside the cor. is a disturbed iron pipe, 40" long, 2" dia. Remove the iron pipe from the area.

From the corner

N.0°38'09"E.,

75 ft., enter creek bottom, bears N.65°W. and S.50°E.

110 ft., creek, 3 ft. wide, course N.40°W.

S.89°28'00"E.,

65 ft., enter creek bottom, bears N.50°W. and S.30°E.

120 ft., creek, 6 ft. wide, course N.40°W.

280 ft., leave creek bottom, bears N.60°W. and S.45°E.

A search was made for all original line trees along the South ½ mile bet. secs. 27 and 28 and none were recovered.