

TOWNSHIP 21 RANGE 09 POINT IDENTIFIER # 400300

PRIMARY CORNER DESCRIPTION Cor. Secs. 21, 22, 27 & 28

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Alonzo Gesner, Deputy Surveyor, under Contract #608, dated April 17, 1893 - (DCSO rec. Vol. 2 Page(s) 943)

-----  
Set chittemwood post, 4½ ft. long, 4" sq., 24" in the ground, for cor. of secs. 21, 22, 27 & 28, marked T21S S22 on NE, R9W S27 on SE, S28 SW, S21 on NW faces, with 2 notches on the S and 3 notches on the E edges; from which

- A Cedar, 30" dia., bears N.42°30'E., 50 lks., mkd: T21S R9W S22 BT.
- A Cedar, 18" dia., bears S.66°30'E., 45 lks., mkd: T21S R9W S27 BT.
- A Hemlock, 16" dia., bears S.33°30'W., 42 lks., mkd: T21S R9W S28 BT.
- A Maple, 24" dia., bears N.80°15'W., 17 lks., mkd: T21S R9W S21 BT.

Douglas Co. Surveyors Office - Gary Langlitz - John E. Nordling - Jan. 15, 1975 - C.S. File 57/17-6

-----  
Found - An orig. BT, a 24" Maple, now a well-rotted stump. We find good scribe marks on the reverse face. The orig. NE & SW BTs are missing. We find a 34" Cedar stump in the record position of the orig. SE BT. It is covered by logging debris & we cannot identify it as an orig. BT.

At the corner point as determined at record bearing & distance from the one remaining orig. BT a 24" Maple, now a stump which bears N.80¼°W., 11.2 ft. we set a 1"x30" iron pipe with brass cap attached mkd:

COUNTY SURVEYORS	T 21 S
OFFICE	<u>S 21</u>   <u>S 22</u>
1975	S 28   S 27
	R 9 W

and mark the following BT:  
A 13" Hemlock bears N.16°E., 54.5 ft. scribed "T21S R9W S22 CS BT"  
Compass declination setting: 20° East.

Fd. Ok by Les Roberts 3/1983 - M 94-4

Tony Hostetter - For: Roseburg Resources - January 2000 - C. S. File 65/30-4 thru 7

-----  
Found - 1975 Douglas Co. brass cap & accessories as described by Les Robert in 1983 (M94-4)  
12" Alder, "IP"tag bears S.20°W. 54.7 ft. to center.

continued next page

TOWNSHIP 21 RANGE 09 POINT IDENTIFIER # 400300

PRIMARY CORNER DESCRIPTION Cor. Secs. 21, 22, 27 & 28

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New BTs- 10" Fir, faced & marked W/"X", BT tag, bears N.54°E., 10.9 ft. to 6" spike placed in root collar.  
12" Alder, marked w/"X", BT tag, bears S.88°E., 25.7 ft. to 6" spiked placed in root collar.  
20" Fir, faced & marked w/"X", BT tag, bears S.21°W., 98.1 ft. to spike placed in root collar.