

TOWNSHIP 21 RANGE 09 POINT IDENTIFIER # 400540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 9 & 10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Alonzo Gesner, Deputy Surveyor, under Contract #608, dated April 17, 1893 - (DCSO rec. Vol. 2 Page(s) 950)

-----  
Set Fir post, 4½' long, 6" sq. 24" in the ground on flat for ¼ sec. cor., from which

A D.Fir, 52" dia., bears N.70°E., 120 lks., mkd: ¼ S BT.

A D.Fir, 30" dia., bears S.65°W., 43 lks., mkd: ¼ S BT.

BLM dependent resurvey by Peter A. Peterson, Cadastral Surveyor, under Group #350 & 511, surveyed April 1966/May 1967 - (DCSO records, Vol. 34 Page(s) 14244)

-----  
Point for ¼ sec. cor. of secs. 9 & 10, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked:

¼  
S 9|S 10  
T21S R9W  
1966

from which

A Fir, 18" dia., bears S.34°E., 33 lks., mkd: ¼ S10 BT.

A Fir, 16" dia., bears S.14°W., 11 lks., mkd: ¼ S9 BT.

Fd. Ok by L. Roberts, 11/1981 - M 90-13

Fd. Ok 12/1990 - M 111-27