

PRIMARY CORNER DESCRIPTION Cor. Secs. 4 & 9 only (East side)

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Alonzo Gesner, Deputy Surveyor, under Contract #608, dated April 17, 1893 - (DCSO rec. Vol. 2 Page(s) 950)

-----  
Set Alder post, 4½ ft. long, 4" sq., 24" in the ground on steep hill side, sloping North for cor. of secs. 3, 4, 9, & 10, mkd: T21S S3 on the NE., R9W S10 on the SE, S9 on the SW., and S4 on the NW faces with 5 notches on the S and 3 notches on the E edges, from which

- A Fir, 36" dia., bears N.12°30'E., 290 lks., mkd: T21S R9W S3 BT.
- A Fir, 80" dia., bears S.82°30'E., 260 lks., mkd: T21S R9W S10 BT.
- An Alder, 6" dia., bears S.70°W., 77 lks., mkd: T21S R9W S9 BT.
- A Fir, 30" dia., bears N.13°30'W., 225 lks., mkd: T21S R9W S4 BT.

GLO survey by Alonzo Gesner, Deputy Surveyor, under Contract #608, dated April 17, 1893 - (DCSO rec. Vol. 2 Page(s) 966)

-----  
N.89°33'E., on true line between secs. 4 & 9 107.81 chs. Intersected N & S line 32.45 chs. North of the SW cor. of Sec. 3.

Set Alder post, 5 ft. long, 4" sq., 24" in the ground on steep hill side sloping E for closing cor. to Secs. 4 & 9 mkd. S9 on the S, T21S R9W on the W & S4 on the N faces with 5 grooves on the S & 3 grooves on the W sides, from which

- A Fir, 24" dia., bears S.89°E., 30 lks., mkd: CC T21S R9W S 4 & 9 BT.
- A Fir, 24" dia., bears S.38°W., 7 lks., mkd: T21S R9W S9 BT.
- A Fir, 26" dia., bears N.58°W., 22 lks., mkd: T21S R9W S4 BT.

BLM dependent resurvey by Peter A. Peterson, Cadastral Surveyor, under Group #350 & 511, surveyed April 1966/May 1967 - (DCSO records, Vol. 34 Page(s) 14258)

-----  
True point for the closing cor. of secs. 4 & 9  
Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked: T 21 S

CC S 4 | S 3  
S 9 |  
R 9 W  
1966

from which

continued next page

TOWNSHIP 21 RANGE 09 POINT IDENTIFIER # 400611

PRIMARY CORNER DESCRIPTION Cor. Secs. 4 & 9 only (East side)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A Hemlock, 8" dia., bears S.39°W., 19 lks., mkd: T21S R9W S9 CC BT.

A Maple, 26" dia., bears N.80°W., 50 lks., mkd: T21S R9W S4 CC BT.

From this point the ¼ sec. cor. of secs. 3 only, bears N.0°04'W., 7.92 chs.

FD. Ok by L. Robert, Nov. 1981 - M 90-13

Fd. Ok 12/1990, M 11-60