

TOWNSHIP 21 RANGE 09 POINT IDENTIFIER # 400614

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 3 only (West)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Alonzo Gesner, Deputy Surveyor, under Contract #608, dated April 17, 1893 - (DCSO rec. Vol. 2 Page(s) 952)

Set hemlock post, 4½ ft. long, 4" sq. 24" in the ground on hill side sloping NE for ¼ sec. cor. mkd. ¼ S on the W face from which
A Fir, 24" dia., bears N.68°30'E., 39 lks., mkd: ¼ S BT.
A Fir, 24" dia., bears N.32°W., 53 lks., mkd: ¼ S BT.

BLM dependent resurvey by Peter A. Peterson, Cadastral Surveyor, under Group #350 & 511, surveyed April 1966/May 1967 - (DCSO records, Vol. 34 Page(s) 14247)

The ¼ sec. cor. of sec. 3 only, determined at record dist. from the orig. BTs:
A Fir, 56" dia., bears N.68½°E., 39 lks., with fragmentary scribe marks visible on opened blaze.
A Fir, 56" dia., bears N.37°W., 53 lks., with healed blaze. (Rec. N.32°W.)
At the corner point
Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked:
|¼
|T21S
|S 3
|R9W
|1966
from which a new BT
A Hemlock, 12" dia. bears S.44°E., 60 lks. mkd: ¼ S3 BT

Fd. Ok 12/90 - M111-61