

TOWNSHIP 21 RANGE 09 POINT IDENTIFIER # 400700

PRIMARY CORNER DESCRIPTION C C for Secs. 3 & 4 only, (North)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Alonzo Gesner, Deputy Surveyor, under Contract #608 -dated April 17, 1893 - (DCSO records Vol. 3 Page(s) 953)

(at point of intersection, 13.75 chs. East of cor. to 33 & 34)

I set Alder post 4½ ft. long, 4" sq., 24" in the ground on steep hill side sloping SW. for closing cor. to secs. 3 & 4 at point of intersection marked CC T21S on the S.; R9W S3 on the E.; and S4 on the W. faces with 3 grooves on the E. and W. faces, from which

A Fir 30" dia., bears S.67°30'E., 68 lks. dist. mkd. T21S R9W S3 BT.

A Fir 30" dia., bears S.13°30'W., 47 lks. dist. mkd. T21S R9W S4 BT.

A Fir 16" dia., bears N.57°W., 58 lks. dist. mkd. CC T21S R9W S3 & 4 BT.

BLM Resurvey by Thomas A. Tillman and Joseph S. Gawron, Cadastral Engineers, under Group #306, surveyed May 1953/Oct. 1954 - (DCSO records Vol. 29 Page(s) 12451)

The closing cor. of secs. 3 & 4, bears North, 0.36 chs. dist., monumented with a Fir post 4½ ft. long, 4" square, firmly set 18" in the ground, from which the original bearing trees:

A Fir 40" dia., bears S.67½°E., 68 lks. dist. plainly blazed and healed.

A sawed Fir stump 40" dia., bears S.13½°W., 47 lks. dist., plainly blazed and healed.

A Fir 30" dia., bears N.57°W., 58 lks. dist., plainly blazed and healed.

BLM resurvey by Peter A. Peterson, Cadastral Surveyor, under Group #'s 350 & 511, surveyed Apr. 1966/May 1967 (DCSO records Vol. 34 Page(s) 14248)

True point for the closing cor. of secs. 3 and 4.
Set an iron post 28" long, 2½" dia., 25" in the ground, with brass cap marked:

T 20 S R 9 W
S 34

S 4 | S 3
T 21 S | R 9 W
CC
1966

from which
(Cont. Next Page)

TOWNSHIP 21 RANGE 09 POINT IDENTIFIER # 400700

PRIMARY CORNER DESCRIPTION C.C. for Secs. 3 & 4 only (North)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A Fir 10" dia., bears S.40°E., 32 lks. dist. mkd. T21S R9W
S3 CC BT.
A Fir 14" dia., bears S.46°W., 56 lks. dist. mkd. T21S R9W
S4 CC BT.

From this point, the original closing cor. of secs. 3 & 4
bears N.0°03'E., 0.375 chs. dist., monumented with a Fir post
4" sq., extending 3 ft. above ground, firmly set, witnessed
as described in the official record of the 1853 resurvey.

(From the same point, the cor. of secs. 33 & 34 only T20S
R9W, bears S.89°28'W., 13.48 chs. dist.)

Ronald L Rice - For: Oxbow Timber 1 LLC - Nov. 2015 - M170-29

Found - BLM brass cap dated 1966
Record 10" fir bearing S.40°E., 32 lks. -down rotted
38" D.Fir bears S.46°W., 37' - healed face
New BTs- 14" D.Fir bears S.48°E., 26.71- blazed, scribed T21S
R9W S3 CC BT
13" a fir bears N.81°W., 22.6', blazed, scribed X BT
48" D.Fir snag bears N.81°W., 35.2' -face scar