

TOWNSHIP 21 RANGE 09 POINT IDENTIFIER # 440100

PRIMARY CORNER DESCRIPTION South 1/4 Cor. Sec. 34 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Alonzo Gesner, Deputy Surveyor, under Contract #608 -dated April 17, 1893 - (DCSO records Vol. 2 Page(s) 895)

Set sandstone 14x7x7 ins., 9" in ground for ¼ sec. cor. marked ¼ on the N face, from which

A Cedar, 14" dia., bears N.9°30'E., 35 lks., mkd: ¼ S BT.

A Hemlock, 6" dia., bears S.48°E., 12 lks., mkd: ¼ S BT.

Dependent resurvey by Boyd W. Peterson & John A. Farmer, Cadastral Surveyors, under Group #1791, surveyed Oct. 1995/Feb. 1998. (DCSO records Vol. 52 Page(s) 19856)

Point for the ¼ sec. cor. of secs. 34 only, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T21S R9W

¼ S 34

T22S

1996

from which

A fir, 9" diam., bears N.14°E., 5½ lks., mkd. X BT.

A fir, 9" diam., bears N.6½°W., 26½ lks., mkd. ¼ S34 BT.

Deposit a magnet in a white plastic case at base of stainless steel post.