

TOWNSHIP 21 RANGE 09 POINT IDENTIFIER # 440200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 27 & 34

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Alonzo Gesner, Deputy Surveyor, under Contract #608, dated April 17, 1893 - (DCSO rec. Vol. 2 Page(s) 942)  
-----  
Set Hemlock post, 4½ ft. long, 4" sq., 24" in the ground on steep hillside sloping East for ¼ sec. cor., mkd: ¼ S on the North face; from which  
    A Fir, 30" dia., bears N.8°E., 18 lks., mkd: ¼ S BT.  
    A Fir, 50" dia., bears S.4°W., 31 lks., mkd: ¼ S BT.

David Edwards - For: Roseburg Resources - June 2000 - M 135-6  
-----  
Found - 1½" x 40" iron pipe & Orig. BT stumps  
          9" Fir S.10°E., 14.61 ft.  
New BTs- 12" Fir, S.25°W., 20.69 ft.  
          15" Fir, S.86°W., 10.06 ft.  
          8" Fir, N.24°W., 6.15 ft.

BLM Dependent resurvey by Joseph M. Mannix, Cadastral Surveyor under Group No. 2721, surveyed June/Aug. 2013 - (DCSO records Vol. 58 Page(s) 23167-8)  
-----  
The ¼ sec. cor. of secs. 27 & 34, perpetuated by person(s) unknown, and further perpetuated by Edwards, in 2000; monumented with a steel pin, 48" long, 5/8" dia., firmly set, projecting 28" above ground, with an alum. cap (properly) mkd from which the remains of an original bearing tree  
    A decayed fir stump, 3½ ft. high, 21" dia., bears N.19°E., 11.9 ft., with a burnt healed blaze. (Record, N.8°E.) and the bearing trees mkd. by Edwards  
    A fir, 17" dia., bears S.83¼°W., 9.7 ft., with a healed blaze.  
    A fir, 11" dia., bears N.11°W., 5.7 ft., with no scribe marks visible on a partially healed blaze.  
At the corner point  
Set a stainless steel post, 28" long, 2½" dia., 23" in the ground, in a collar of stone, with brass cap mkd.  
          T21S R9W  
          ¼  $\frac{S\ 27}{S\ 34}$   
          2013  
Lying alongside the cor. is a disturbed iron pipe, 60" long, 2" dia. Remove the steel pin and the iron pipe from the area.  
Corner is located on a ridge, bears N.25°W. and S.35°W.

continued next page

1

TOWNSHIP 21 RANGE 09 POINT IDENTIFIER # 440200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 27 & 34

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff Lorsung- 8/28/2023 - C.S. File 67/56-62

-----

Found - 2013 BLM brass cap (properly mkd)  
21" D.Fir S.83¼°W., 9.7 ft fully healed single blaze  
11" D.Fir N.11°W., 5.7 ft fully healed single blaze.  
Steel post 2 ft. West.

Note - Compass decl. 14½°E.  
Oregon Coordinate Reference System  
Cottage Grove - Canyonville Zone  
N 318793.397 E 52520.334