

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 22 & 27

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Alonzo Gesner, Deputy Surveyor, under Contract #608, dated April 17, 1893 - (DCSO rec. Vol. 2 Page(s) 944)

Set post, 4½ ft. long, 4" sq., 24" in the ground on hillside sloping South for ¼ sec. cor., mkd: ¼ S on N face; from which
A Fir, 20" dia., bears S.40°30'W., 8 lks., mkd: ¼ S BT.
A Fir, 36" dia., bears N.29°W., 19 lks., mkd: ¼ S BT.

BLM dependent resurvey by Peter A. Peterson, Cadastral Surveyor, under Group #350 & 511, surveyed April 1966/May 1967 - (DCSO records, Vol. 34 Page(s) 14264)

The ¼ sec. cor. of secs. 22 & 27 determined at the record bearing & distance from the orig. BTs:

A sawed fir stump, 48" dia., bears N.29°W., 19 lks., with scribe marks ¼ S BT visible on opened blaze.

A sawed fir stump, 24" dia., bears S.40½°W., 8 lks., with healed blaze.

At the corner point

Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked:

¼ $\frac{S\ 22}{S\ 27}$

T21S R9W

from which new BTs

A Fir, 7" dia., bears N.42°E., 21 lks., mkd: ¼ S22 BT.

A Fir, 6" dia., bears S.32°E., 39 lks., mkd: ¼ S27 BT.

An iron post, 2" dia. extending 30" above ground loosely set bears S.5°E., 6 lks., with steel cap mkd: ¼ S22 27.

Fd. & used on BLM dependent resurvey by John A. Farmer, Cadastral Surveyor, under Group #1399, surveyed Aug./Sept. 1987 - (DCSO records Vol. 48 Page(s) 18454-5)

Tony Hostetter - For: Roseburg Resources - January 2000 - C. S. File 65/30-4 thru 7

Found - 1987 BLM brass cap
24" Fir, face evident, bears N.43°E., 13.9 ft. to center.
20" Fir, face evident, bears S.20°E., 25.9 ft. to center.
40" Fir, OBT, scribing visible, bears N.22°W., 12.6 ft. to center.
2½" iron pipe w/cap, unrecorded monument, bears S.13°W., 3.9 ft.

New BT - 10" Fir, faced & marked w/"X" BT tag, bears N.88°W., 20.5 ft. to 6" spike placed in root collar.