

TOWNSHIP 21 RANGE 09 POINT IDENTIFIER # 440500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 10 & 15

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Alonzo Gesner, Deputy Surveyor, under Contract #608, dated April 17, 1893 - (DCSO rec. Vol. 2 Page(s) 949)

Set Fir post, 4½ ft. long, 4" sq., 24" in the ground on hillside sloping SW for ¼ secs. cor. mkd. ¼ S on the N face, from which
 A Fir, 16" dia., bears S.70°E., 28 lks., mkd: ¼ S BT.
 A Fir, 6" dia., bears N.25°W., 26 lks., mkd: ¼ S BT.

BLM dependent resurvey by Norman J. McDonald, Cadastral Surveyor, under Group #350 April 1963/ - (DCSO records, Vol. 32 Page(s) 13137)

The ¼ sec. cor. of secs. 10 & 15 determined at the record bearing & distance from the orig. BTs:
 A Fir, 16" dia., bears N.25°W., 26 lks., with fragmentary scribe marks visible on open blaze.
 A Fir, 32" dia., bears S.70°E., 28 lks., with partially open blaze.
At the corner point
Set an iron post, 30" long, 2½" dia., 26" in the ground, with brass cap marked:
 T21S R9W
 ¼ S 10
 S 15
 1963
from which a new BT
 A Hemlock, 10" dia. bears N.20°W., 38 lks., mkd: ¼ S10 BT.

BLM dependent resurvey by Peter A. Peterson, Cadastral Surveyor, under Group #350 & 511, surveyed April 1966/May 1967 - (DCSO records, Vol. 34 Page(s) 14243)

The ¼ sec. cor. of secs. 10 & 15, monumented with an iron post, 2½" dia., extending 5" above ground, firmly set, with brass cap marked & witnessed as described in the official record of the 1963 remonumentation.

Fd. as per record T. Hostetter 9/2023 - M183-19