

TOWNSHIP 21 RANGE 09 POINT IDENTIFIER # 500200

PRIMARY CORNER DESCRIPTION Cor Secs 26, 27, 34, & 35

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GL0 survey by Alonzo Gesner, Deputy Surveyor, under Contract #608, dated April 17, 1893 - (DCSO rec. Vol. 2 Page(s) 928-9)  
-----  
Set Hemlock post 4½ ft. long 4" sq. 24" in the ground for cor. to secs. 26, 27, 34, & 35 mkd. T21S S26 on the NE, R9W S35 on the SE, S34 on the SW & S27 on the NW faces with 1 notch on the S and 2 notches on the E edges, from which  
A Maple, 12" dia., bears N.4°30'E., 57 lks., mkd: T21S R9W S26 BT.  
A Fir, 24" dia. bears S.20°E., 79 lks mkd: T21S R9W S35 BT  
A Hemlock, 20" dia., bears S.59°W., 47 lks., mkd: T21S R9W S34 BT.  
An Alder, 16" dia., bears N.43°30'W., 16 lks., mkd: T21S R9W S27 BT.

Les Roberts - For: International Paper Co. - 11/30/1981 - M 89-74  
-----  
Found - 30" Fir stump bears S.20°E., 52.1 ft., no marks. 1894 BT.  
24" Hemlock stump bears S.59°W., 31 ft., no marks. 1894 BT.  
Group of Maples bears N.4½°E., 37.6 ft., no marks. 1894 BT  
Set - 1½" x 36" IP & brass cap.  
New BTs- 12" Fir bears N.63°E., 33.5 ft. scribed.  
14" Fir bears S.45°W., 39.4 ft. scribed.  
14" Fir bears S.73°W., 33.8 ft. scribed.  
15" Fir bears N.44°W., 35.3 ft. scribed.

David Edwards - For: Roseburg Resources - June 2000 - M135-6  
-----  
Monument per M89-74 destroyed by rd. construction.  
Reset from Fd. BTs per M 89-74.  
Note: Distances from last 2 BTs are reversed.  
Set - 5/8" x 40" steel pin w/alum. cap.

BLM Dependent resurvey by Joseph M. Mannix, Cadastral Surveyor under Group No. 2721, surveyed June/Aug. 2013 - (DCSO records Vol. 58 Page(s) 23162-3)  
-----  
The cor. of secs. 26, 27, 34, & 35, perpetuated and utilized by Roberts, in 1981, and further perpetuated and utilized by Edwards, in 2000; monumented with a steel pin, 44" long, 5/8" dia., firmly set, with top flush with road surface, and an aluminum cap mkd.  
T21S R9W  
S 27 | S 26  
S 34 | S 35  
LS 2339  
2000

continued next page

TOWNSHIP 21 RANGE 09 POINT IDENTIFIER # 500200

PRIMARY CORNER DESCRIPTION Cor Secs 26, 27, 34, & 35

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

from which the remains of the original bearing trees  
A decayed fir stump, size indeterminate, bears S.20°E.,  
52.1 ft., no marks visible.  
A very decayed hemlock stump, size indeterminate, bears  
S.59°W., 31.0 ft., no marks visible.  
and the remains of the bearing trees mkd. by Roberts  
A fir stump, 7 ft. high, 19" dia., bears N.62°E., 32.9  
ft., with a healed blaze.  
A fir stump, 6 ft. high, 20" dia., bears S.45½°E., 39.4  
ft., with a healed blaze.  
A root hole bears S.72½°W., 33.8 ft., alongside of which  
is an uprooted fir, 28" dia., with a healed blaze.  
A fir, 26" dia., bears N.44°W., 33.6 ft., with a healed  
blaze.

At the corner point

Set a stainless steel post, 28" long, 2½" dia., 40" in the  
ground, with a brass cap mkd.

T 21 S R 9 W  
S 27 | S 26  
S 34 | S 35  
2013

and new reference monuments

An iron rod, 30" long, 5/8" dia., set 30" in the ground,  
bears N.20°33'02" E, 30.30 ft., with aluminum cap mkd.  
RM T21S R9W 30.3 FT TO COR S26 2013, and an arrow  
pointing to the cor.

An iron rod, 30" long, 5/8" dia., set 30" in the ground,  
bears S.45°45'04" E, 32.56 ft., with aluminum cap mkd.  
RM T21S R9W 32.6 FT TO COR S35 2013, and an arrow  
pointing to the cor.

An iron rod, 30" long, 5/8" dia., set 30" in the ground,  
bears S.49°13'41" W, 30.18 ft., with aluminum cap mkd.  
RM T21S R9W 30.2 FT TO COR S34 2013, and an arrow  
pointing to the cor.

Remove steel pin from the area.

Corner is located in a gravel road, 5 ft. East of the center,  
12 ft. wide, bears N. 10° W and South, in curve.

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff  
Lorsung- 8/28/2023 - C.S. File 67/56-61

Found - BLM brass cap (properly mkd) buried in East tire  
track of road, not dug up.

Robert's BTs

19" D.Fir 7' high stump N.62°E. 32.9 ft healed blaze  
20"x6 ft. D.Fir stump S.45½°E., 39.4 ft healed blaze  
27"x15 ft. D.Fir N.44°W., 33.6 ft. healed blaze.

continued next page

TOWNSHIP 21 RANGE 09 POINT IDENTIFIER # 500200

PRIMARY CORNER DESCRIPTION Cor Secs 26, 27, 34, & 35

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Reference monuments by BLM -  
5/8"x30" iron rod with alum. cap N.20°33'02"E., 30.3 ft., stamped T21S R9W 30.3 FT to COR S26 2013, arrow pointing to corner.  
5/8"x30" iron rod with alum. cap S.45°45'04"E., 32.56 ft., stamped T21S R9W 32.6 FT to COR S35 2013, arrow pointing to corner.  
5/8"x30" iron rod S.49°13'41"W., 30.18 ft. under fallen log not looked for.  
Note - Compass decl. 14½°E.  
Oregon Coordinate Reference System  
Cottage Grove - Canyonville Zone  
N 318877.721 E 55182.912