

TOWNSHIP 21 RANGE 09 POINT IDENTIFIER # 500235

PRIMARY CORNER DESCRIPTION Line tree on line between Secs. 26 & 27

|             |                   |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

GLO survey by Alonzo Gesner, Deputy Surveyor, under Contract #608, dated April 17, 1893 - (DCSO rec. Vol. 2 Page(s) 930)

-----  
A fir, 20" dia., a line tree marked with 2 notches on the N and S sides.

Les Roberts - For: International Paper Co. - 11/30/1981 - M 89-74

-----  
Found - 44" Fir with 2 blazes on North and south sides.  
Set - 1½"x36" iron pipe & brass cap reference monument  
N.0°31'27"E., 5.00' from the center of tree.  
12" Alder, N.89°E., 38.6' (scribed)  
50" Fir, S.36°W., 14.6' (scribed)

BLM Dependent resurvey by Joseph M. Mannix, Cadastral Surveyor under Group No. 2721, surveyed June/Aug. 2013 - (DCSO records Vol. 58 Page(s) 23164)

-----  
The original line tree bet. secs. 26 and 27, a fir, 51" dia., with 2 notches on the north and south faces, perpetuated by Roberts, in 1981, and now becomes an angle point, from which the accessories mkd. by Roberts  
An alder, 14" dia., bears N.83¼°E., 38.9 ft., with scribe marks RM S26 BT visible on bark.  
A fir, 55" dia., bears S.48½°W., 11.1 ft., with a healed blaze.  
An iron post, 1½" dia., firmly set, projecting 24" above ground, bears N.3°22'15" E, 4.20 ft., with a brass cap, oriented easterly, mkd. PLS 1039 WP T21S S27 S26 R9W 1981.  
From the angle point  
S.0°55'26" E., 200 ft., creek, 15 ft. wide, course N.70°W.