TOWNSHIP 21 RANGE 09 POINT IDENTIFIER # 500240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 26 & 27

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Alonzo Gesner, Deputy Surveyor, under Contract #608, dated April 17, 1893 - (DCSO rec. Vol. 2 Page(s) 930)

Set cedar post, 4½ ft. long, 4" sq., 24" in the ground for ¼ sec. cor., mkd: ¼ S on the W face; from which
A Cedar, 10" dia., bears N.55°30'E., 36 lks., mkd: ¼ S BT.
A Cedar, 20" dia., bears S.51°30'W., 35 lks., mkd: ¼ S BT.

Les Roberts - For: International Paper Co. - Nov. 30, 1981 - M 90-13 & M 89-74

Found - No evidence found of orig. corner.
Set - 1½" x 36" IP & brass cap at proportionate distance.
37" Fir bears N.81°W., 21.0 ft. scribed.
44" Fir bears S.7°E., 44.4 ft. scribed.

BLM Dependent resurvey by Joseph M. Mannix, Cadastral Surveyor under Group No. 2721, surveyed June/Aug. 2013 - (DCSO records Vol. 58 Page(s) 23164-5)

The ¼ sec. cor. of secs. 26 and 27, reestablished by proportionate measurement by Roberts, in 1981. There is no remaining evidence of the original cor., therefore this point is accepted as a careful and faithful reestablishment of the cor.; monumented with an iron post, 1½" dia., firmly set, projecting 3" above ground, with a brass cap mkd.

PLS 1039
¼
S 27|S 26
1981

from which the bearing trees mkd. by Roberts
A fir, 55" dia., bears S.8½°E., 43.8 ft., with a healed blaze.
A fir, 40" dia., bears N.83°W., 21.2 ft., with a healed blaze.
Alongside the cor. is an iron rod, 1/2" dia., projecting 3 ft. above ground.