

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 14 & 15

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Alonzo Gesner, Deputy Surveyor, under Contract #608, dated April 17, 1893 - (DCSO rec. Vol. 2 Page(s) 935)

-----  
Set Fir post, 4½ ft. long, 4" sq., 24" in the ground on steep hillside sloping North for ¼ sec. cor., mkd: ¼ S on the W face, from which;

A Hemlock, 4" dia., bears N.67°12'E., 50 lks. mkd: ¼ S BT.

A Fir, 10" dia., bears N.22°W., 57 lks., mkd: ¼ S BT.

BLM dependent resurvey by Peter A. Peterson, Cadastral Surveyor, under Group #350 & 511, surveyed April 1966/May 1967 - (DCSO records, Vol. 34 Page(s) 14235)

-----  
The ¼ sec. cor. of secs. 14 & 15 determined at the record bearing & distance from the only remaining orig. BT:

A Fir, 21" dia., bears N.22°W., 57 lks., with scribe marks ¼ visible on opened blaze.

At the corner point

Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked:

¼  
S 15|S 14  
T21S R9W  
1966

from which a new BT:

A Hemlock, 6" dia., bears N.2°E., 49 lks., mkd: ¼ S14 BT.

Clyde Mulkins - For: I.P. Timber Operating Co. LTD - March 1996 - M 123-67

-----  
Found - 21" D.Fir stump with visible scribes bears N.22°W., 37.6'.

Gone - 6" Hemlock, (rec. N.2°E., 49 lks.)

Set - 3/4" x 12" alum. rod with a 3¼" alum. cap in sand stone.

7" alder bears N.56°E. 41.2' bark scribed "¼ S14 BT"

5' steel fence post bears S.3°W., 21.4'.

5' steel fence post bears N.72°W., 46.8'.

Both fence posts are on the North edge of a gravel road.