

TOWNSHIP 21 RANGE 09 POINT IDENTIFIER # 500500

PRIMARY CORNER DESCRIPTION Cor. Secs 10, 11, 14, & 15

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Alonzo Gesner, Deputy Surveyor, under Contract #608, dated April 17, 1893 - (DCSO rec. Vol. 2 Page(s) 935)

Set Cherry post, 4½ ft. long, 4" sq., 24" in the ground in a huckleberry thicket for cor. of secs. 10, 11, 14, & 15, marked T21S S11 on NE, R9W S14 on SE, S15 SW, S10 on NW faces with 4 notches on the S and 2 notches on the E edges; from which
A Fir, 18" dia. bears N.28°E. 30 lks. mkd: T21S R9W S11 BT
A fir, 10" dia. bears S.30°E. 17 lks. mkd: T21S R9W S14 BT
A Fir, 11" dia. bears S.65°W. 24 lks. mkd: T21S R9W S15 BT
A Fir, 18" dia., bears N.68°45'W., 31 lks., mkd: T21S R9W S10 BT.

BLM dependent resurvey by Peter A. Peterson, Cadastral Surveyor, under Group #350 & 511, surveyed April 1966/May 1967 - (DCSO records, Vol. 34 Page(s) 14235)

The cor. of secs. 10, 11, 14, & 15, determined at the record bearing & dist. from the orig. BTs:
A Fir, 45" dia. bears N.28°E., 30 lks., with healed blaze.
A fir, 18" dia. bears S.30°E. 17 lks. with healed blaze.
A Fir, 18" dia. bears S.65°W. 24 lks. with no marks visible on partly opened blaze.
A Fir, 18" dia. bears N.68¾°W., 31 lks. with healed blaze.
At the corner point
Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked:
T21S R9W
S 10|S 11
S 15|S 14
1966

BLM Dependent resurvey by Joseph M. Mannix, Cadastral Surveyor under Group No. 2721, surveyed June/Aug. 2013 - (DCSO records Vol. 58 Page(s) 23166)

The cor. of secs. 10, 11, 14, and 15, monumented with an iron post, 2½" dia., firmly set, projecting 6" above ground, with a brass cap mkd.
T21S R9W
S 10|S 11
S 15|S 14
1966
from which the remains of the original bearing trees
A fir, 55" dia., bears N.28°E., 19.8 ft., with a healed blaze.
A decayed fir stump, size indeterminate, bears S.30°E., 11.2 ft., with a healed blaze in bark fragment. cont

TOWNSHIP 21 RANGE 09 POINT IDENTIFIER # 500500

PRIMARY CORNER DESCRIPTION Cor. Secs. 10, 11, 14, & 15

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A fir, 21" dia., bears S.65°W., 15.8 ft., with an X at breast height and a healed blaze.
A decayed fir stump, 41" dia., bears N.68¾°W., 20.5 ft., with a healed blaze.
and new bearing trees
A fir, 10" dia., bears S.45°E., 14.2 ft., mkd. T21S R9W S14 BT.
A fir, 7" dia., bears N.50°W., 7.8 ft., mkd. X BT.
NAD 1983 (2011)
Latitude: 43°44'56.80"N. Longitude: 123°44'41.51"W.

Fd. as per record T. Hostetter 9/2023 - M183-19