

TOWNSHIP 21 RANGE 09 POINT IDENTIFIER # 540300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 23 & 26

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Alonzo Gesner, Deputy Surveyor, under Contract #608, dated April 17, 1893 - (DCSO rec. Vol. 2 Page(s) 932)

Set a sandstone, 12 x 12 x 6", in the ground on steep hillside sloping E for 1/4 sec. cor., mkd: 1/4 on N. face; from which

A Cedar, 20" dia., bears N.82°E., 114 lks., mkd: 1/4 S BT.

A Cedar, 20" dia., bears S.2°E., 43 lks., mkd: 1/4 S BT.

Dependent resurvey by Boyd W. Peterson, Cadastral Surveyor, under Group #1735, surveyed June 1994/March 1995. (DCSO rec Vol. 52 Pgs 19693-4)

Point for the 1/4 sec. cor. of secs. 23 & 26, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 28" long, 2 1/2" diam., 24" in the ground, with brass cap mkd.

T21S R9W

1/4 S 23

S 26

1994

from which

A fir, 16" diam., bears S.7 1/2°W., 56 lks., mkd. 1/4 S26 BT.

A fir, 13" diam., bears N.35°W., 21 lks., mkd. 1/4 S23 BT.

Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.