

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 14 & 23

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Alonzo Gesner, Deputy Surveyor, under Contract #608, dated April 17, 1893 - (DCSO rec. Vol. 2 Page(s) 934)

Set sandstone 14x12x6" 10" in the ground on steep hillside sloping E for ¼ sec. cor. mkd. ¼ on the N face, from which
A Fir, 60" dia., bears N.68½°W., 137 lks., mkd: ¼ S BT.
A Hemlock, 6" dia. bears S.47°45'W., 63 lks., mkd: ¼ S BT.

BLM dependent resurvey by Peter A. Peterson, Cadastral Surveyor, under Group #350 & 511, surveyed April 1966/May 1967 - (DCSO records, Vol. 34 Page(s) 14234)

Point for ¼ sec. cor. of secs. 14 & 23, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28" long, 2½" dia., 25" in the ground, with brass cap marked:

¼ S 14
 S 23
T21S R9W
1966

from which

A Fir, 4" dia., bears N.17°E., 67 lks., mkd: ¼ S14 BT.
A Fir, 6" dia., bears S.5°E., 68 lks., mkd: ¼ S23 BT.

Clyde Mulkins - For: I.P. Timber Operating Co. LTD - March 1996 - M 123-67

Found - 1966 BLM brass cap.
17" D.Fir with a healed face bears N.17°E., 42.2', (rec. 67 lks.)
6" D.Fir bears S.5°E., 68 lks. - uprooted
New BTs- 13" D.Fir bears N.60°W., 28.7', scribed "¼ S14 BT"
12" D.Fir bears S.7°E., 11.9', scribed "¼ S23 BT"
12" D.Fir bears N.80°E., 18.9', scribed "¼ S14 BT"