

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 2

Alias	Description

BLM dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2286, surveyed Oct. 2009 - (DCSO records Vol. 56 Page(s) 22347)

Point for the center ¼ sec. cor. of sec. 2, at intersection of the N and S and the E and W center lines.
Set a stainless steel post, 28 ins. long, 2½" dia., 22 ins. in the ground, with brass cap mkd.

T21S R9W
C ¼ S 2
2010

from which

- A fir, 12" dia., bears N.50¾°E., 29.0 ft., mkd. C¼ S2 BT.
- A fir, 12" dia., bears S.63°W., 18.1 ft., mkd. X BT, with

Mag Nail left side center.

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Corner is located E., 1½ ft., of a fir, 1 ft. dia., and E., 60 ft., of draw, drains N.25°W.

From this cor., a point established by person(s) unknown, bears N.63°50'04"W., 3.50 ft., determined at record distances from the faces of the remains of the BTs mkd. by person(s) unknown utilizing information documented on a corner card held at the BLM Coos Bay District Office

- A burned cedar stump, 42" dia., bears N.50¾°E., 27.2 ft., no marks visible.

- A burned fir stump with metal cap, 54" dia. bears S.14½°W. 12.4 ft., no marks visible.

There is no filed survey or other known record documenting who established this point or how it was established, therefore this point was not utilized for control during this survey.