

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Alonzo Gesner, Deputy Surveyor, under Contract #608 -dated April 17, 1893 - (DCSO records Vol. 2 Page(s) 895)

Set Hemlock post, 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 35, 36, 1 and 2, marked T21S S36 on the NE.; R9W S1 on the SE.; T22S S2 on the SW. and S35 on the NW faces with 1 notch on the E & 5 notches on the W. edges, from which
A Hemlock 8" dia., bears N.82°45'E., 43 lks. dist. mkd. T21S R9W S36 BT.
A Fir 24" dia., bears S.44°E., 47 lks. dist. mkd. T22S R9W S1 BT.
A Fir 24" dia., bears S.1°30'W., 31 lks. dist. mkd. T22S R9W S2 BT.
A Hemlock 24" dia., bears N.23°W., 46 lks. dist. mkd. T21S R9W S35 BT.

GLO survey by Elmer O. Worrick, Deputy Surveyor, under Contract #632, dated April 28, 1894 - (DCSO records Vol. 4 Page(s) 1658-59)

Intersected the N. bdy. of T., 120 lks. W. of the corner to secs. 1, 2, 35 and 36, T21S., which is a post, 2 ft. above ground, 4" sq., firmly set, mkd. T21S S36 on the E., R9W S1 on the SE., T22S S2 on the SW., and S35 on the NW. faces with 1 notch on the E., and 5 notches on the W. edges, from which
A Hemlock 8" dia., bears N.82°45'E., 43 lks. dist. mkd. T21S R9W S36 BT.
A Fir 24" dia., bears S.44°E., 47 lks. dist. mkd. T22S R9W S1 BT.
A Fir 24" dia., bears S.1°30'W., 31 lks. dist. mkd. T22S R9W S2 BT.
A Hemlock 24" dia., bears N.23°W., 46 lks. dist. mkd. T21S R9W S35 BT.
Destroyed marks on the Fir BT in Sec. 1 and changed the marks on the BT in sec. 2, to T21S R9W S35 and 36 BT.
Also obliterated the marks on the SE. and SW. faces of the post, and marked the NW. face R9W S35.
Set a Hemlock post, 4½ ft. long, 4" sq. 24" in ground at point of intersection for closing corner to secs. 1 & 2. Marked CC on the S, R9W S1 on the E, and 5 grooves on the W faces, from which
A Hemlock, 7" dia., bears S.74°E., 37 lks., mkd: T22S R9W S1 BT.
A Fir, 24" dia. bears S.82°W., 79 lks. mkd: T22S R9W S2 BT
A Hemlock, 22" dia., bears N.32°E., 31 lks., mkd: CC T22S R9W S1 & 2 BT.

TOWNSHIP 21 RANGE 09 POINT IDENTIFIER # 578100

PRIMARY CORNER DESCRIPTION CC Secs. 1 & 2 only, T22-9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Dependent resurvey by Boyd W. Peterson & John A. Farmer, Cadastral Surveyors, under Group #1791, surveyed Oct. 1995/Feb. 1998. (DCSO records Vol. 52 Page(s) 19855)

A point established as the closing corner of sections 1 and 2 by person(s) unknown monumented with an iron pipe, ½ in. diam., firmly set, projecting 8 ins. above ground.

****Note****

BLM does not monument or re-monument this point, nor do they say if they accept this as the true position for the CC or if they do not accept it. (DCSO 10/4/1999 jc)