

PRIMARY CORNER DESCRIPTION So. Sec. cor. for 35 and 36 only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Alonzo Gesner, Deputy Surveyor, under Contract #608 -dated April 17, 1893 - (DCSO records Vol. 2 Page(s) 895)

-----  
Set Hemlock post, 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 35, 36, 1 and 2, marked T21S S36 on the NE.; R9W S1 on the SE.; T22S S2 on the SW. and S35 on the NW faces with 1 notch on the E. and 5 notches on the W. edges, from which

- A Hemlock 8" dia., bears N.82°45'E., 43 lks. dist. mkd. T21S R9W S36 BT.
- A Fir 24" dia., bears S.44°E., 47 lks. dist. mkd. T22S R9W S1 BT.
- A Fir 24" dia., bears S.1°30'W., 31 lks. dist. mkd. T22S R9W S2 BT.
- A Hemlock 24" dia., bears N.23°W., 46 lks. dist. mkd. T21S R9W S35 BT.

GLO survey by Elmer O. Worrick, Deputy Surveyor, under Contract #632, dated April 28, 1894 - (DCSO records Vol. 4 Page(s) 1658-59)

-----  
Intersected the N. bdy. of T., 120 lks. W. of the corner to secs. 1, 2, 35 and 36, T21S., which is a post, 2 ft. above ground, 4" sq., firmly set, mkd. T21S S36 on the E., R9W S1 on the SE., T22S S2 on the SW., and S35 on the NW. faces with 1 notch on the E., and 5 notches on the W. edges, from which

- A Hemlock 8" dia., bears N.82°45'E., 43 lks. dist. mkd. T21S R9W S36 BT.
- A Fir 24" dia., bears S.44°E., 47 lks. dist. mkd. T22S R9W S1 BT.
- A Fir 24" dia., bears S.1°30'W., 31 lks. dist. mkd. T22S R9W S2 BT.
- A Hemlock 24" dia., bears N.23°W., 46 lks. dist. mkd. T21S R9W S35 BT.

Destroyed marks on the Fir BT in Sec. 1 and changed the marks on the BT in sec. 2, to T21S R9W S35 and 36 BT.  
Also obliterated the marks on the SE. and SW. faces of the post, and marked the NW. face R9W S35.

H. T. Lewis, Eng. #722 - Oct. 18, 1939 - C.S. File 16/55 (and "old" corner book, page 28)

-----  
I found all witness trees in place but the Hemlocks which are the trees for sec. 35 and 36, have been killed by fire. I therefore set a Hemlock post 4" long, 4" dia. 18" in ground, from which

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION So. Sec. cor. for 35 & 36 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A Hemlock 9" dia., bears N.47½°W., 34 ft. dist. mkd. T21S R9W S35 BT Eng. 722.  
A Fir 36" dia., bears N.60°E., 65 ft. dist. mkd. T21S R9W S36 BT Eng. 722.

B.L.M. Resurvey by Boyd Peterson, under group No. 1735; June 1994 thru March 1995 -(DCSO records Vol. 52 Page(s) 19690-91)

-----  
Found iron pipe, ½ in. diam., firmly set 3 ins. below surface of the ground, from which the remains of an original bearing tree mkd. by Gesner, reported obliterated by Worrick, recovered by Daily, Adams, Mintor, and Counts:

A fir stump, 34 ins. diam., bears S.44°E., 47 lks. dist., with scribe marks S/9W S1 BT visible on open blaze.

At the corner point

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T21S R9W  
S35 S36  
S 1  
T22S R9W  
1994

and new bearing trees

A fir, 5 ins. diam., bears N.16°E., 26½ lks. dist., mkd. T21S R9W S36 BT.

A fir, 10 ins. diam., bears N.56¼°W., 22½ lks. dist., mkd. T21S R9W S35 BT.

Deposit iron pipe and white "DEEP-1" magnetic marker at base of stainless steel post.

Fd. & used on Dependent resurvey by Boyd W. Peterson & John A. Farmer, Cadastral Surveyors, under Group #1791, surveyed Oct. 1995/Feb. 1998. (DCSO records Vol. 52 Page(s) 19855)