

TOWNSHIP 21 RANGE 09 POINT IDENTIFIER # 600300

PRIMARY CORNER DESCRIPTION Cor. Secs. 23, 24, 25, & 26

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Alonzo Gesner, Deputy Surveyor, under Contract #608 -dated April 17, 1893 - (DCSO rec. Vol. 2 Page(s) 915-6)

Set fir post 5 ft. long 5" sq. 24" in the ground for Cor. to secs. 23, 24, 25, & 26 marked T 21 S S 24, on NE, R 9 W S 25 on SE, S 26 on the SW, and S 23 on the NW faces with 2 notches on the S and 1 notch on the E edges, from which
A Hemlock, 10" dia., bears N.12°30'E., 10 lks., mkd: T21S R9W S24 BT.
A Fir, 48" dia., bears S.80°E., 54 lks., mkd: T21S R9W S25 BT.
A Hemlock, 10" dia., bears S.47°30'W., 8 lks., mkd: T21S R9W S26 BT.
A Hemlock, 5" dia., bears N.27°W., 9 lks., mkd: T21S R9W S23 BT.

Dependent resurvey by Boyd W. Peterson, Cadastral Surveyor, under Group #1735, surveyed June 1994/March 1995. (DCSO rec Vol. 52 Pgs 19690)

Point for the cor. of secs. 23, 24, 25 & 26, at proportionate distance; there is no remaining evidence of the original corner.
Set a stainless steel post, 28" long, 2½" diam., 22" in the ground, with brass cap mkd. T21S R9W
S 23 S 24
S 26 S 25
1994

from which
A fir, 10" diam., bears N.82½°E., 84½ lks., mkd. T21S R9W S24 BT.
A fir, 16" diam., bears S.55½°E., 74 lks., mkd. T21S R9W S25 BT.
A fir, 19" diam., bears S.48°W., 20 lks., mkd. T21S R9W S26 BT.
A fir, 16" diam., bears N.62½°W., 9 lks., mkd. T21S R9W S23 BT.
Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.