

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 23 & 24

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Alonzo Gesner, Deputy Surveyor, under Contract #608 -dated April 17, 1893 - (DCSO rec. Vol. 2 Page(s) 918)

Set fir post 4 ft. long 4" sq. 24" in the ground on steep hill side sloping NW for ¼ Sec. cor. marked ¼ S on the W. face, from which

A Fir, 12" dia., bears N.35°E., 9 lks., mkd: ¼ S BT.

A Fir, 8" dia., bears S.45°38'W., 14 lks., mkd: ¼ S BT.

Dependent resurvey by Boyd W. Peterson, Cadastral Surveyor, under Group #1735, surveyed June 1994/March 1995. (DCSO rec Vol. 52 Pgs 19691-2)

The 1/4 sec. cor. of secs. 23 & 24, determined at record bearing & distance from the remains of an original bearing tree:

A roothole, bears N.35°E., 9 lks., with a down fir alongside, 15" diam., with scribe marks BT visible on open blaze.

Set a stainless steel post, 28" long, 2½" diam., 14" in the ground to solid rock, and in a mound of stone, 3 ft. base to top, with brass cap mkd.

T21S R9W
¼
S 23 S 24
1994

from which

A fir, 7" diam., bears S.70°E., 7 lks., mkd. 1/4 S24 BT.

A fir, 6" diam., bears N.23°W., 7½ lks., mkd. X BT.

Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.

From this point, control station No. 41228 established by the Control Survey Unit of the Oregon State Office, Bureau of Land Management, in 1994, at latitude 43°45'01.751"N. and longitude 123°46'48.183" W., bears N.61°39'20"W., 253.971 chs. (mean bearing and sea level distance); monumented with an aluminum cap, 3¼" diam., firmly set flush with the ground, mkd. EC 41228-GPS-1994.