TOWNSHIP 21 RANGE 9 POINT IDENTIFIER # 600440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 13 & 14

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Alonzo Gesner, Deputy Surveyor, under Contract #608, dated April 17, 1893 - (DCSO rec. Vol. 2 Page(s) 921)

Set Hemlock post 4½ ft. long 4" sq. 24" in the ground on point of hill sloping West for ¼ sec. cor. mkd. ¼ S. on the W face, from which

A Hemlock, 20" dia., bears S.85°E., 14 lks., mkd: ¼ S BT.
A Fir, 5" dia., bears N.11°W., 31 lks., mkd: ¼ S BT.

BLM dependent resurvey by Peter A. Peterson, Cadastral Surveyor, under Group #350 & 511, surveyed April 1966/May 1967 - (DCSO records, Vol. 34 Page(s) 14226)

Point for the ¼ sec. cor. of secs. 13 & 14, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28 long, 2½" dia., 22" in the ground with brass cap marked:

¼
S 14|S 13
T21S | R9W
1966

from which

A Fir, 6" dia., bears S.49½°E., 16 lks., mkd: ¼ S13 BT.
A Fir, 8" dia., bears S.43°W., 34 lks., mkd: ¼ S14 BT.

Clyde Mulkins - For: I.P. Timber Operating Co. LTD - March 1996 - M 123-67

Found - 1966 BLM brass cap.
13" D.Fir with a healed face bears S.43°W., 34 lks.
15" D.Fir with a healed face bears S.42°E., 16 lks.
(Rec. S49½°E.)
New BTs- 10" D.Fir bears N.46°W., 17.4', scribed "¼ S14 BT"
17" D.Fir bears N.27°W., 12.2', scribed "¼ S14 BT"