

PRIMARY CORNER DESCRIPTION Cor. Secs. 11, 12, 13, & 14

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Alonzo Gesner, Deputy Surveyor, under Contract #608, dated April 17, 1893 - (DCSO rec. Vol. 2 Page(s) 922)

-----  
Set Hemlock post, 5 ft. long, 4½" sq., 24" in the ground in hemlock thicket, for cor. of secs. 11, 12, 13, & 14 marked T21S S12 on NE, R9W S13 on SE, S14 SW, & S11 on NW faces with 4 notches on the S & 2 notches on the N edges; from which

- A Hemlock, 10" dia., bears N.32°E., 22 lks., mkd: T21S R9W S12 BT.
- A Hemlock, 12" dia., bears S.32°30'E., 25 lks., mkd: T21S R9W S13 BT.
- A Fir, 50" dia., bears S.78°W., 76 lks., mkd: T21S R9W S14 BT.
- A Hemlock, 15" dia., bears N.10°W., 45 lks., mkd: T21S R9W S11 BT.

BLM dependent resurvey by Peter A. Peterson, Cadastral Surveyor, under Group #350 & 511, surveyed April 1966/May 1967 - (DCSO records, Vol. 34 Page(s) 14227)

-----  
The cor. of secs. 11, 12, 13, & 14, determined at the record bearing & dist. from the orig. BTs:

- A Hemlock snag, 13" dia., bears N.32°E., 22 lks., with opened & decayed blaze.
- A decayed Hemlock stump, 14" dia., bears S.32½°E., 25 lks., with no marks remaining.
- A decayed Fir stump, 60" dia., bears S.78°W., 76 lks., with marks remaining.
- A Hemlock snag, 20" dia., bears N.10°W., 45 lks., with scribe marks T21S visible on opened blaze.

At the corner point

Set an iron post, 28" long, 2½" dia., 25" in the ground, with brass cap marked:

T21S R9W  
S 11|S 12  
S 14|S 13  
1966

- A Hemlock, 6" dia., bears N.40°E., 24 lks., mkd: T21S R9W S12 BT.
- A Fir, 6" dia. bears S.50°E., 9 lks. mkd: T21S R9W S13 BT.
- A Fir, 5" dia. bears S.45°W., 17 lks. mkd: T21S R9W S14 BT
- A Hemlock, 5" dia., bears N.25°W., 34 lks., mkd: T21S R9W S11 BT.

continued next page

TOWNSHIP 21 RANGE 09 POINT IDENTIFIER # 600500

PRIMARY CORNER DESCRIPTION Cor. Secs. 11, 12, 13, & 14

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

Clyde Mulkins - For: I.P. Timber Operating Co. LTD - March 1996 - M 123-67

-----

Found - 1966 BLM brass cap at the corner.  
14" Hemlock with a healed face bears N.25°W., 34 lks  
14" Hemlock with a healed face bears N.40°E., 24 lks  
15" D.Fir stump, with a partial healed face bears  
S.47°E., 5.9'. (Rec. S.50°E.)  
Gone - 5" D.Fir, (rec. S.45°W., 5.9 ft)  
New BTs- 15" D.Fir bears S.62.°W., 10.3', scribed "S14 BT"  
17" D.Fir bears S.25°E., 26.5', scribed "S13 BT"