

TOWNSHIP 21 RANGE 09 POINT IDENTIFIER # 600540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 11 & 12

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Alonzo Gesner, Deputy Surveyor, under Contract #608, dated April 17, 1893 - (DCSO rec. Vol. 2 Page(s) 924)

Set fir post 4½ ft. long 4" sq. 24" in the ground (on a flat) for ¼ Sec. cor. mkd. ¼ S on the W. face, from which
A Fir, 10" dia., bears N.15°E., 24 lks., mkd: ¼ S BT.
A Fir, 12" dia., bears N.49°W., 7 lks., mkd: ¼ S BT.

BLM dependent resurvey by Peter A. Peterson, Cadastral Surveyor, under Group #350 & 511, surveyed April 1966/May 1967 - (DCSO records, Vol. 34 Page(s) 14228-9)

The ¼ sec. cor. of secs. 11 & 12 determined at record bearing & distance from the orig. BTs:

A Fir snag, 16" dia., bears N.15°E., 24 lks., with scribe marks SBT visible on opened blaze.

The stump hole of a fallen fir, 28" dia., bears N.49°W., 7 lks., with healed blaze.

At the corner point

Set an iron post, 28" long, 2½" dia., 22" in the ground, with brass cap marked:

¼
S 11|S 12
T21S R9W
1966

from which new BTs

A Fir, 6" dia., bears N.62°E., 28 lks., mkd: ¼ S12 BT.

A Fir, 6" dia., bears S.44°W., 16 lks., mkd: ¼ S11 BT.

Fd. Ok by Les Roberts, PLS 1039 - For: Int. Paper Co. - 8/19/1985 - M99-32 & C.S. File 63/18-2(C)

Mark Smalley - For: Roseburg Forest Products - Mar. 13, 1997 - C.S. 65/13-9D

Found - 1966 BLM IPBC

16" Fir snag, N.15°E., 15.4' scribe visible

24" downed Fir, N.49°W., 5' No marks

10" Fir, N.64°E., 17.9' good healed face

12" Fir, S.42°W., 11.1' good healed face

New Accessories -

8" Fir, N.8°W., 13.5' scribed "¼ SBT"

9" Fir, S.45°E., 9.8' scribed "¼ SBT"