

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 24 & 25

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Alonzo Gesner, Deputy Surveyor, under Contract #608 -dated April 17, 1893 - (DCSO rec. Vol. 2 Page(s) 917)

Set dogwood post 4½ ft. long 4" sq. 24" in the ground on hill side sloping SE for ¼ Sec. cor. marked ¼ S on the N. face, from which

A Fir, 30" dia., bears N.23°15'E., 54 lks., mkd: ¼ S BT.

A fir, 5" dia., bears S.42°E., 12 lks., mkd: ¼ S BT.

Dependent resurvey by Boyd W. Peterson, Cadastral Surveyor, under Group #1735, surveyed June 1994/March 1995. (DCSO rec Vol. 52 Pgs 19689)

Beginning at the 1/4 sec. cor. of secs. 24 & 25, determined at record bearing & distance from the remains of original bearing trees:

A decayed fir stump, 33" diam., bears N.23¼°E., 54 lks., with axe marks visible.

A decayed fir stump, 13" diam., bears S.42°E., 12 lks., with scribe marks BT visible on opened blaze.

At the corner point

Set a stainless steel post, 28" long, 2½" diam., 24" in the ground, with brass cap mkd.

T21S R9W

¼ S 24

S 25

1994

and new bearing trees

A fir, 14" diam., bears N.35°E., 21½ lks., mkd. ¼ S24 BT.

A fir, 16" diam., bears S.66¼°E., 66½ lks., mkd. ¼ S 25 BT

Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.