

TOWNSHIP 21 RANGE 9 POINT IDENTIFIER # 640400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 13 & 24

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Alonzo Gesner, Deputy Surveyor, under Contract #608, dated April 17, 1893 - (DCSO rec. Vol. 2 Page(s) 920)

-----  
Set Maple post 4½ ft. long 4" sq. 24" dia., in the ground on steep hill side sloping NE, for ¼ sec. cor. marked ¼ S on the N face, from which

A Fir, 48" dia., bears N.8°30'E., 41 lks., mkd: ¼ S BT.

A Fir, 40" dia., bears S.49°30'E., 50 lks., mkd: ¼ S BT.

BLM dependent resurvey by Peter A. Peterson, Cadastral Surveyor, under Group #350 & 511, surveyed April 1966/May 1967 - (DCSO records Vol. 34 Page(s) 14225)

-----  
The ¼ sec. cor. of secs. 13 & 24, determined at record bearing & distance from the orig. BTs:

A sawed Fir stump, 50" dia., bears N.8½°E., 41 lks. with opened & burned blaze.

A stump hole, bears S.49½°E., 50 lks.

At the corner point

Set an iron post, 28" long, 2½" dia., 22" in the ground, with brass cap marked:

¼ S 13  
S 24  
T21S R9W  
1966

A Fir, 4" dia., bears N.41°W., 23 lks., mkd: X BT.

A Fir, 6" dia., bears S.6½°W., 40 lks., mkd: ¼ S24 BT.