

TOWNSHIP 21 RANGE 9 POINT IDENTIFIER # 640500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 12 & 13

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Alonzo Gesner, Deputy Surveyor, under Contract #608, dated April 17, 1893 - (DCSO rec. Vol. 2 Page(s) 922)

Set Hemlock post, 4½ ft. long, 4" sq., 24" in the ground for ¼ sec. cor., mkd: ¼ S on N face; from which
 A Hemlock, 6" dia., bears N.54°W., 4 lks., mkd: ¼ S BT.
 A Hemlock, 12" dia., bears S.53°E., 52 lks., mkd: ¼ S BT.

BLM dependent resurvey by Peter A. Peterson, Cadastral Surveyor, under Group #350 & 511, surveyed April 1966/May 1967 - (DCSO records, Vol. 34 Page(s) 14227-8)

Point for the ¼ sec. cor. of secs. 12 & 13, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28 long, 2½" dia., 22" in the ground with brass cap marked:
 ¼ S 12
 S 13
 T21S R9W
 1966
from which
 A Fir, 10" dia., bears N.11°W., 11 lks., mkd: ¼ S12 BT.
 A Fir, 5" dia., bears S.65°E., 14 lks., mkd: ¼ S13 BT.

Fd. Ok by Les Roberts 8/19/1985 - C.S. 63/18-2(B) & M 99-32