

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 12

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Les Roberts, PLS 1039 - For: Int. Paper Co. - 8/19/1985 - M99-32 & C.S. File 63/18-2(G)  
-----  
Found - Old squared wooded post set by BLM Administrative staff compass survey. (No record)  
Set - 2½"x30" alum. pipe & cap mkd: T21S R9W S12 C¼ COR 1985 PLS 1039" Buried purple magnetic marker under pipe. See filed survey for procedures. BLM Administrative wooden post bears N.89°36'E., 16.64 ft.  
New BTs- 10" Fir, N.33°E., 1.4 ft. to spike. (Scribed/alum. washer/painted red)  
10 Fir, S.52°E., 10.7 ft. to spike. (Scribed/alum. washer/painted red)  
Accessories -  
Set metal fence post, with land survey monument sign wired to, beside alum. pipe.  
Note - Corner lies 100 ft. West of road junction.

---

Gary Smither - 2/2005 - C.S. File 65/54-11  
-----  
Found - At the ¼ corner found 3" Aluminum Cap on a 2½" aluminum pipe with a steel post near the corner. This monument was established in 1985, county survey number M99-32  
15" D.Fir N.33°E., 1.4 ft., with healed face, spike side center and BT tag.  
14" D.Fir S.52°E., 10.7 ft, with healed face, spike side center and BT tag.  
New - 23" D.Fir N.4°W., 41.8 ft., scribed T21 R9 C¼ S12 BT, spike side center and BT tag.  
20" D.Fir S.84°W., 32.3 ft., scribed T21 R9 C¼ S12 BT, spike side center and BT tag.