

TOWNSHIP 21 RANGE 09 POINT IDENTIFIER # 640600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 1 & 12

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Alonzo Gesner, Deputy Surveyor, under Contract #608, dated April 17, 1893 - (DCSO rec. Vol. 2 Page(s) 925)

Set post, 4½ ft. long, 4½" sq., 24" in the ground for ¼ sec. cor., mkd: ¼ S on th N face; from which
A Hemlock, 16" dia., bears N.26°E., 13 lks., mkd: ¼ S BT.
A Hemlock, 12" dia., bears S.32°E., 25 lks., mkd: ¼ S BT.

BLM dependent resurvey by Peter A. Peterson, Cadastral Surveyor, under Group #350 & 511, surveyed April 1966/May 1967 - (DCSO records, Vol. 34 Page(s) 14230)

The ¼ sec. cor. of secs. 1 & 12 determined at the record bearing & distance from the only remaining BT:

A rotted Hemlock stump, 34" dia., bears N.26°E., 13 lks., with scribe marks ¼ S visible on decayed blaze.

At the corner point

Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked:

¼ $\frac{S \ 1}{S \ 12}$
T21S R9W
1967

from which the new BTs

A Fir, 12" dia., bears N.52°E., 14 lks., mkd: ¼ S1 BT.

A Fir, 10" dia., bears S.47°W., 30 lks., mkd: ¼ S12 BT.

Fd. Ok by Les Roberts, PLS 1039 - For: Int. Paper Co. - 8/19/1985 - M99-32 & C.S. File 63/18-2(A)

Mark Smalley - For: Roseburg Forest products - Mar. 13, 1997 - C.S. 65/13-9E

Found - 1967 BLM IPBC & 1¼" I.P bent over
24" Fir, N.54°E., 9.1' good healed face
20" Fir, S.47°W., 19.4' good healed face

New Accessories -

11" Fir, N.76°W., 24.4' scribed "¼ S BT"

10" Hemlock, S.3°E., 36' scribed "¼ S BT"