

PRIMARY CORNER DESCRIPTION SE Cor. Sec. 36 (SE. Tsp. Cor.)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 202 survey dated March 11, 1874 (DCSO records Vol. 4 Page(s) 1589)

Set Fir post, 4 ft. long, 20" in ground, 5" dia., for cor. to Tps. 21 and 22 S., Rs. 8 & 9 W, from which
A Fir 30" dia., bears N.35°E., 52 lks. dist.
A Fir 24" dia., bears S.25°E., 28 lks. dist.
A Fir 16" dia., bears S.15°W., 36 lks. dist.
A Fir 16" dia., bears N.75°W., 50 lks. dist.

GLO survey by Alonzo Gesner, Deputy Surveyor under Contract #608, dated April 17, 1893 (DCSO records Vol. 2 Page(s) 894)

I commenced at cor. to Tps. 21 and 22 S. Rgs. 8 and 9 W, which I established as follows:
Set a Fir post, 4 ft. long, 4" sq., 24" in the ground marked T21S S31 on the NE., R8W S6 on the SE.; T22S S1 on the SW.; and R9W S36 on the NW. faces, with 6 notches on the N, E, S, and W. edges, from which
A Fir 24" dia., bears S.25°E., 28 lks. dist. mkd. T22S R8W S6 BT.
A Fir 20" dia., bears S.15°W., 36 lks. dist. mkd. T22S R9W S1 BT.
The stumps of the bearing trees in secs. 31 and 36 were standing, and all agreeing with notes furnished me by the U.S. Surveyor General. I marked:
A Fir 8" dia., bears N.69°E., 22 lks. dist. mkd. T21S R8W S31 BT.
A Fir 6" dia., bears N.78°W., 27 lks dist. mkd. T21S R9W S36 BT.
(Owing to the heavy timber and dense undergrowth, I could not take observations at this corner.)

Fd. and Used in GLO survey by Elmer O. Worrick, Deputy Surveyor under Contract #632, dated April 28, 1894. (DCSO records, Vol. 4 Pages 1614-15) and page 1703)

GLO survey by Norman D. Price, Cadastral Engineer, and Geo. Rigby, Assoc. Cadastral Engineer, under Contract #282, surveyed May/Aug. 1945 (DCSO records Vol. 27 Page(s) 11373)

The cor. of Tps. 21 and 22 S., Rs. 8 and 9 W., the locus of which is determined by reference to the record measurements from each of the old bearing trees.
At point for corner,
Set an iron post, 3 ft. long, 3" dia., 28" in the ground, for corner, with brass cap marked: (Cont. Next Page)

PRIMARY CORNER DESCRIPTION SE Cor. Sec. 36 (SE Tsp. Cor.)

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

T 21 S	
R 9 W	R 8 W
S 36	S 31
S 1	S 6
T 22 S	
1945	

from which

- A badly charred Fir stub, 36" dia., bears N.37°E., 52 lks. dist. on which no marks remain. (Old BT)
- A dead Fir 11" dia., bears N.69°E., 22 lks. dist. mkd. T21S R8W S31 BT. (An old BT mkd. by Gesner in 1894)
- A badly charred Fir 48" dia., bears S.21½°E., 28 lks. dist. on which no marks remain. (Old BT)
- A badly charred Fir stump 40" dia., bears S.15°W., 36 lks. dist. on which no marks remain. (Old BT)
- A fallen Fir 12" dia., bears N.78°W., 27 lks. dist. mkd. T21S R9W S36 BT. (An old BT mkd. by Gesner in 1894)
- A badly charred Fir stump 28" dia., bears N.75°W., 50 lks. dist. on which no marks remain. (Old BT)
- A dead Fir 38" dia., bears N.36°E., 163 lks. dist. mkd. T21S R8W S31 BT. (New BT)
- A Fir 48" dia., bears S.38°E., 296 lks. dist. mkd. T22S R8W S6 BT. (New BT)
- A Fir 48" dia., bears S.18½°W., 247 lks. dist. mkd. T22S R9W S1 BT. (New BT)
- A dead Fir 38" dia., bears N.12½°W., 19 lks. dist. mkd. T21S R9W S36 BT. (New BT)

Douglas Co Surveyors Office - Milo E Godfrey, Deputy - M Stone & Wm Stoffel, crew - Sept. 25, 1963 - CS File 52/14-72

Found - 1945 Cadastral Brass cap, bulldozed out and buried in ground, lying across corner position.
 38" Fir stump N.12½°W., 12.5 ft.
 48" Fir stump S.18½°W., 163.0 ft. axe marks in bark "S1 BT"
 Burned remnants of big Fir stump S.21½°E., 18.5 ft.
 38" Fir stump N.36°E., 107.6 ft.
 36" Fir stump N.37°E., 34.3 ft.
 No scribe marks found - No trace of other old BTs.
 Reset Govt. brass cap in proper position.
 Rescribe 38" Fir stump N.12½°W., 12.5 ft. "T21S R9W S36". (broke scribe)
 No live trees available.

Fd. Ok by V. McLind 10/1997 M127-77