

TOWNSHIP 21 RANGE 09 POINT IDENTIFIER # 700140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 36; & 31, T21-8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W. P. Wright, U.S. Deputy Surveyor, under Contract #486, dated August 1, 1883 (DCSO records Vol. 2 Page(s) 887)

Set post 4" dia., 4 ft. long, with marked stone, 12" in ground for ¼ sec. cor., marked ¼ Section on W. face, from which
A Cedar 36" dia., bears West, 21 lks. dist. mkd. ¼ S BT.
A Cedar 15" dia., bears S.35°E., 23 lks. dist. mkd. ¼ S BT

GLO Resurvey by Norman D. Price and George Rigby, Cadastral Engineers, under Group #282, Surveyed May/Aug. 1945 - (DCSO records Vol. 27 Page(s) 11380)

Proportional measurement.
Set an iron post 3 ft. long, 1" dia., 28" in the ground for ¼ sec. cor., with brass cap mkd. ¼
S 36|S 31
1945
from which
A Fir 44" dia., bears N.83°E., 442 lks. mkd. ¼ S31 BT.
A Fir 22" dia., bears N.27°W., 141 lks. mkd. ¼ S36 BT.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - V. Tracy & C Putnam, crew - April/May 1962 - C.S. File 52/14-16

Ronald L. Rice, Ward NW - Dec. 2011 - C.S. File 65/72-47

Found - 2½" GLO brass cap dated 1945 with the following accessories:
None were recovered
New - Corner was referenced and removed to protect it from logging, then reset after logging based on my references. Corner is located in recent clear cut with limited accessories.
32" D.Fir stump bears N.41°E., 17.66' to head of 60D nail in center of face
31" D.Fir stump bears N.54°W., 25.70' to head of 60D nail in center of face
35" D.Fir bears S.26°E., 144.3' blazed, scribed "¼ S31 BT"
Note - Corner has steel post adjacent to it. All BTs have red painted bands and yellow tags.
Compass Declination 16° east