

PRIMARY CORNER DESCRIPTION Sec. Cor. for 25 & 36; 30 & 31, T21-8

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by W. P. Wright, U.S. Deputy Surveyor, under Contract #486, dated August 1, 1883 (DCSO records Vol. 2 Page(s) 888)

- 
- A Fir 4" dia., for cor. to secs. 30, 31, 25 and 36, marked T21S S30 on NE.; R8W S31 on SE.; R9W S36 on SW.; and S25 on NW. faces, with 5 notches on N. and 1 on S. edges, from which
- A Fir 12" dia., bears N.55°E., 7 lks. dist. mkd. T21S R8W S30 BT.
  - A Fir 12" dia., bears S.28°E., 16 lks. dist. mkd. T21S R8W S31 BT.
  - A Fir 5" dia., bears N.57°W., 5 lks. dist. mkd. T21S R9W S25 BT.
  - A Fir 6" dia., bears S.36°W., 16 lks. dist. mkd. T21S R9W S36 BT.

GLO survey by Alonzo Gesner, Deputy Surveyor, under Contract #608 -dated April 17, 1893 - (DCSO records Vol. 2 Page(s) 913-14)

- 
- Intersected the E. bdy. of Tp., (T21S R9W) 23 lks. S. of the cor., which is a post greatly decayed. I destroyed it and re-established the cor. as follows:
- Set a Fir post 5 ft. long, 5" sq., 24" in the ground on hill side sloping W., marked T21S S30 on the NE.; R8W S31 on the SE.; R9W S36 on the SW.; and S25 on the NW. faces, with 1 notch on the S. and 5 notches on the N. edges, from which
- A Fir 12" dia., bears N.53°E., 63 lks. dist. mkd. T21S R8W S30 BT.
  - A Fir 48" dia., bears S.44°E., 88 lks. dist. mkd. T21S R8W S31 BT.
  - A Fir 36" dia., bears S.15°W., 111 lks. dist. mkd. T21S R9W S36 BT.
  - A Fir 12" dia., bears N.72°W., 143 lks. dist. mkd. T21S R9W S25 BT.

The BTs of the original survey had been destroyed, only the stumps standing and agreeing with notes furnished me by the U.S. Sur. General.

GLO Resurvey by Norman D. Price and George Rigby, Cadastral Engineers, under Group #282, Surveyed May/Aug. 1945 - (DCSO records Vol. 27 Page(s) 11380)

-----

(After a careful investigation, it is developed that Gesner's recorded retracement of this line is entirely fictitious, that it is a deliberate fabrication on his part for the purpose of justifying his own work and creating a limiting

(Cont. Next Page)

TOWNSHIP 21 RANGE 09 POINT IDENTIFIER # 700200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 25 & 36; 30 & 31, T21-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

boundary for T21S R9W., and is therefore rejected as a suitable basis for restoration of lost corners referring to T21S R8W.) (Vol. 27 Pg. 11379)

The Sec. Cor., the locus of which is determined at the record measurements from the Gesner NE. and SE. bearing trees and record bearings from the Gesner SW. and NW. bearing trees.

At the corner point

Set an iron post, 3 ft. long, 2" dia., 28" in the ground, with brass cap mkd:

T 21 S
R 9 W R 8 W
<u>S 25 S 30</u>
S 36 S 31
1945

from which

- A Fir 36" dia., bears N.56°45'E., 63 lks. dist., with blaze healed. (Old BT)
- A Fir 48" dia., bears S.43°E., 88 lks. dist. with blaze healed. (Old BT)
- A sawed Fir stump 48" dia., bears S.15°W., 119 lks. dist. with blaze healed. (Old BT)
- A sawed Fir stump 36" dia., bears N.72°W., 122 lks. dist. with blaze healed. (Old BT)
- A Fir 22" dia., bears S.25½°W., 213 lks. dist. mkd. T21S R9W S36 BT. (New BT)
- A Fir 40" dia., bears N.34°W., 173 lks. dist. mkd. T21S R9W S25 BT. (New BT)