

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for sec. 19 only, T21-8

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by W. P. Wright, U.S. Deputy Surveyor, under Contract #486, dated August 1, 1883 (DCSO records Vol. 2 Page(s) 889)

Set post 4" dia., 4 ft. long, with marked stone 12" in ground for ¼ sec. cor. marked ¼ S on W. face, from which
A Hemlock 6" dia., bears N.82°W., 21 lks. dist. mkd. ¼ S BT.
A Cedar 6" dia., bears N.80°E., 23 lks. dist. mkd. ¼ S BT.

GLO Resurvey by Norman D. Price and George Rigby, Cadastral Engineers, under Group #282, Surveyed May/Aug. 1945 - (DCSO records Vol. 27 Page(s) 11383)

Proportional measurement.
Set an iron post, 3 ft. long, 1" dia., 28" in the ground, for ¼ sec. cor. of sec. 19 only, with brass cap mkd: ¼ S 19 1945
from which
A Hemlock 16" dia., bears S.52°E., 87 lks. dist., mkd. ¼ S19 BT.
A Fir 20" dia., bears S.22½°E., 41 lks. dist. mkd. ¼ S19 BT.

BLM resurvey by Peter A. Peterson, Cadastral Surveyor, under Group #'s 350 & 511, surveyed Apr. 1966/May 1967 (DCSO records Vol. 34 Page(s) 14207-08)

The ¼ sec. cor. of 19 only, monumented with an iron post 1" dia., extending 12" above ground, firmly set, with brass cap marked in 1945,
from which new bearing trees:
A Fir 6" dia., bears N.85°E., 132 lks. dist. mkd. ¼ S19 BT
A Fir 5" dia., bears S.55°E., 52 lks. dist. mkd. ¼ S19 BT.
No evidence of the bearing trees mkd. in 1945 can be found.

Clyde Mulkins, L.S. #2006 - For: IP Timber Lands Operating Co. LTD - Oct. 1995 - M 123-22

Found - 1945 GLO brass Cap
13" D.Fir, bears S.56°E., 33.5', with healed face.
New BTs- 15" D.Fir, bears N.1°W., 12.1', scribed "¼ X BT"
16" D.Fir, bears S.3°W., 9.5', scribed "¼ X BT"
11" D.Fir, bears N.61°W., 10.7', scribed "¼ X BT"